

# **Certificate of Compliance**

Certificate: 80030073 Master Contract: 273488

**Project:** 80030073 **Date Issued:** 2020-03-31

**Issued to:** Ningbo Ginlong Technologies Co., Ltd.

No.57, Jintong Road, Xiangshan Ningbo, Zhejiang, 130 315712

**CHINA** 

**Attention:** Ruyi Pan

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only



Issued by: Magic Zhang
Magic Zhang

### **PRODUCTS**

CLASS 5311 09 - POWER SUPPLIES - Distributed Generation Power Systems Equipment CLASS 5311 89 - POWER SUPPLIES - Distributed Generation Power Systems Equipment - Certified to U.S. Standards

Photovoltaic rapid shutdown system, include: Attenuator and Inverter (Transmitter integrated in the Inverter).

| Model        | Attenuators     | Inverter            | System Ratings           |
|--------------|-----------------|---------------------|--------------------------|
| Photovoltaic | Altenergy Power | Ginlong:            | 500 Vdc maximum          |
| intelligent  | System Inc.:    | RHI-1P5K-HVES-5G;   | system voltage.          |
| module level | RSD-S-PLC-A     | RHI-1P6K-HVES-5G;   | Rapid shutdown time      |
| rapid        | RSD-S-PLC-B     | RHI-1P7K-HVES-5G;   | limit 30s with inverter. |
| shutdown     |                 | RHI-1P7.6K-HVES-5G; |                          |
| system       |                 | RHI-1P8K-HVES-5G;   |                          |
|              |                 | RHI-1P9K-HVES-5G;   |                          |
|              |                 | RHI-1P10K-HVES-5G;  |                          |



 Certificate:
 80030073
 Master Contract:
 273488

 Project:
 80030073
 Date Issued:
 2020-03-31

#### Note:

- 1. For details related to rating, size, configuration, etc., reference should be made to the CSA Certification Record, Certificate of Compliance Annex A, or the Descriptive Report.
- 2. Photovoltaic Rapid Shutdown Function has also been evaluated according to NEC-2017 Section 690.12 applicable requirement.
- 3. Attenuators Input: 8~80Vdc, 15Amax per module, 15A max input short circuit. Attenuators Output: 8~80Vdc, 15Amax, 800W max per module.
- 4. The Rapid shutdown function for the system is initiated by the disconnecting of AC emergency circuit breaker.

## **APPLICABLE REQUIREMENTS**

UL Std. No. 1741-Second Edition - Inverters, Converters, Controllers and Interconnection System Equipment for Use With Distributed Energy Resources (February 15, 2018)

CSA C22.2 No. 330-17 - Photovoltaic rapid shutdown systems



# Supplement to Certificate of Compliance

Certificate: 80030073 Master Contract: 273488

The products listed, including the latest revision described below, are eligible to be marked in accordance with the referenced Certificate.

## **Product Certification History**

| Project  | Date       | Description  |
|----------|------------|--|
| 80030073 | 2020-03-31 | PV Rapid Shutdown System function verification testing, model Photovoltaic |
|          |            | intelligent module level rapid shutdown system. (C/US)                     |