# Product data sheet Characteristics

## QO112L200GRB LOADCTR QO MLO 240V 200A 1PH 12SP NEMA3R





Product availability: Stock - Normally stocked in distribution facility

Price\*: 480.00 USD



#### Main Product or component Load Centre typeproduct or component type Range of productrange QO of product Load centre typeload Main lugs centre type Line Rated CurrentLine 200 A Rated Current Number of spacesnum-12 ber of spaces Short-circuit cur-65 kA rentshort-circuit current Number of circuitsnum-12 ber of circuits Number of tandem cir-0 cuit breakersnumber of tandem circuit breakers PhasePhase 1 phase System VoltageSystem 120/240 V AC Voltage

#### Complementary

AWG gaugeAWG gauge	AWG 6AWG 2/0 (aluminium/copper)	
NEMA degree of protectionNEMA degree of protection	NEMA 3R outdoor	
Cover typecover type	Surface cover	
Device compositiondevice composition	Grounding bar included (not installed)	
Electrical connectionelectrical connection	Lugs	
Wiring configurationwiring configuration	3-wire	
Materialmaterial	Tin plated copper busbar	
Box numberbox number	5R	
Product certificationsproduct certifications	UL listed	

#### Ordering and shipping details

00002 - QO 1PH LC,12-42 CKT,NEMA3R
DE3A
00785901867869
1
Υ
US

### Offer Sustainability

RoHS (date code: YYWW)RoHS (date code: YY-WW)	Compliant  - since  1248  -  Schneider Electric declaration
	of conformity Schneider Electric declaration of conformity
REAChREACh	Reference not containing SVHC above the threshold
Product end of life instructionsProduct end of life intructions	Need no specific recycling operations

Warranty periodWarranty period	18 months