

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 15$ ft							Panel Orientation: Portrait				
Table 1		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	116	116	114	104	95	89	82	77	75	73	69
	10	102	102	102	101	100	95	89	82	77	75	73	69
	20	86	86	86	86	86	86	86	82	77	75	73	69
	30	74	74	74	74	74	74	74	74	74	73	73	69
	40	65	65	65	65	65	65	65	65	65	65	65	65
	50	59	59	59	59	59	59	59	59	59	59	59	59
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	100	90	86	82	75	69	65	60	57	55	53	50
	10	100	90	86	82	75	69	65	60	57	55	53	50
	20	86	86	86	82	75	69	65	60	57	55	53	50
	30	74	74	74	74	74	69	65	60	57	55	53	50
	40	65	65	65	65	65	65	65	60	57	55	53	50
	50	59	59	59	59	59	59	59	59	57	55	53	50
	60	54	54	54	54	54	54	54	54	54	54	53	50
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 3	0	79	71	68	65	59	55	51	48	45	44	42	40
	10	79	71	68	65	59	55	51	48	45	44	42	40
	20	79	71	68	65	59	55	51	48	45	44	42	40
	30	74	71	68	65	59	55	51	48	45	44	42	40
	40	65	65	65	65	59	55	51	48	45	44	42	40
	50	59	59	59	59	59	55	51	48	45	44	42	40
	60	54	54	54	54	54	54	51	48	45	44	42	40
	70	50	50	50	50	50	50	50	48	45	44	42	40
	80	48	48	48	48	48	48	48	48	45	44	42	40
	90	44	44	44	44	44	44	44	44	44	44	42	40

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System
Table 2

 Mean Roof Height: $0 < h \leq 15$ ft Panel Orientation: Portrait

 Roof Angle: $0 < \theta \leq 7$ degrees

Exposure Category: D

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	
Zone 1	0	116	112	107	102	93	86	80	74	70	68	66	62
	10	102	101	101	100	93	86	80	74	70	68	66	62
	20	86	86	86	86	86	85	80	74	70	68	66	62
	30	74	74	74	74	74	74	74	73	70	68	66	62
	40	65	65	65	65	65	65	65	65	65	65	65	62
	50	59	59	59	59	59	59	59	59	59	59	59	59
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	90	81	77	74	68	63	58	55	51	50	48	46
	10	90	81	77	74	68	63	58	55	51	50	48	46
	20	86	81	77	74	68	63	58	55	51	50	48	46
	30	74	74	74	74	68	63	58	55	51	50	48	46
	40	65	65	65	65	65	63	58	55	51	50	48	46
	50	59	59	59	59	59	59	58	55	51	50	48	46
	60	54	54	54	54	54	54	54	54	51	50	48	46
	70	50	50	50	50	50	50	50	50	50	50	48	46
	80	48	48	48	48	48	48	48	48	48	48	48	46
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 3	0	71	64	61	58	54	50	46	43	41	40	38	36
	10	71	64	61	58	54	50	46	43	41	40	38	36
	20	71	64	61	58	54	50	46	43	41	40	38	36
	30	71	64	61	58	54	50	46	43	41	40	38	36
	40	65	64	61	58	54	50	46	43	41	40	38	36
	50	59	59	59	58	54	50	46	43	41	40	38	36
	60	54	54	54	54	54	50	46	43	41	40	38	36
	70	50	50	50	50	50	50	46	43	41	40	38	36
	80	48	48	48	48	48	48	46	43	41	40	38	36
	90	44	44	44	44	44	44	44	43	41	40	38	36

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 15$ ft							Panel Orientation: Portrait				
Table 3		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	116	114	112	106	98	91	85	80	78	75	71
	10	99	97	96	95	92	90	87	85	80	78	75	71
	20	80	80	80	79	78	76	75	73	72	71	71	69
	30	67	67	67	67	67	67	67	66	64	64	63	62
	40	59	59	59	59	59	59	59	59	59	58	58	57
	50	54	54	54	54	54	54	54	54	54	54	54	53
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	100	90	86	83	76	70	66	61	58	56	54	51
	10	99	90	86	83	76	70	66	61	58	56	54	51
	20	80	80	80	79	76	70	66	61	58	56	54	51
	30	67	67	67	67	67	67	66	61	58	56	54	51
	40	59	59	59	59	59	59	59	59	58	56	54	51
	50	54	54	54	54	54	54	54	54	54	54	54	51
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	80	73	69	66	61	57	53	49	46	45	44	41
	10	80	73	69	66	61	57	53	49	46	45	44	41
	20	80	73	69	66	61	57	53	49	46	45	44	41
	30	67	67	67	66	61	57	53	49	46	45	44	41
	40	59	59	59	59	59	57	53	49	46	45	44	41
	50	54	54	54	54	54	54	53	49	46	45	44	41
	60	49	49	49	49	49	49	49	49	46	45	44	41
	70	46	46	46	46	46	46	46	46	46	45	44	41
	80	43	43	43	43	43	43	43	43	43	43	43	41
	90	41	41	41	41	41	41	41	41	41	41	41	41

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

Table 4 Mean Roof Height: $0 < h \leq 15$ ft Panel Orientation: Portrait
 Roof Angle: $7 < \theta \leq 27$ degrees
 Exposure Category: D

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	
Zone 1	0	116	111	109	104	96	89	83	77	72	70	68	65
	10	97	94	93	92	89	87	83	77	72	70	68	65
	20	80	79	78	78	76	74	73	71	69	69	68	65
	30	67	67	67	67	67	66	65	64	63	62	61	60
	40	59	59	59	59	59	59	59	58	57	57	57	56
	50	54	54	54	54	54	54	54	54	53	53	53	52
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	90	82	78	75	69	64	59	56	52	51	49	48
	10	90	82	78	75	69	64	59	56	52	51	49	48
	20	80	79	78	75	69	64	59	56	52	51	49	48
	30	67	67	67	67	67	64	59	56	52	51	49	48
	40	59	59	59	59	59	59	59	56	52	51	49	48
	50	54	54	54	54	54	54	54	54	52	51	49	48
	60	49	49	49	49	49	49	49	49	49	49	49	48
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	73	66	63	60	55	51	48	45	42	41	40	38
	10	73	66	63	60	55	51	48	45	42	41	40	38
	20	73	66	63	60	55	51	48	45	42	41	40	38
	30	67	66	63	60	55	51	48	45	42	41	40	38
	40	59	59	59	59	55	51	48	45	42	41	40	38
	50	54	54	54	54	54	51	48	45	42	41	40	38
	60	49	49	49	49	49	49	48	45	42	41	40	38
	70	46	46	46	46	46	46	46	45	42	41	40	38
	80	43	43	43	43	43	43	43	43	42	41	40	38
	90	41	41	41	41	41	41	41	41	41	41	40	38

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 15$ ft										Panel Orientation: Portrait	
Table 5		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	106	100	97	94	88	84	79	75	72	70	68	65
	10	94	91	89	87	84	81	78	75	72	70	68	65
	20	82	79	78	77	75	72	70	68	66	65	64	62
	30	73	71	70	70	68	66	64	63	61	60	60	58
	40	65	65	65	64	63	61	60	59	57	57	56	55
	50	59	59	59	59	58	57	56	55	54	53	53	52
	60	55	55	55	55	55	54	53	52	51	51	50	49
	70	51	51	51	51	51	51	51	50	49	48	48	48
	80	48	48	48	48	48	48	48	48	48	46	46	45
	90	45	45	45	45	45	45	45	45	45	45	44	44
Zone 2	0	106	100	97	94	88	83	77	72	68	66	64	61
	10	94	91	89	87	84	81	77	72	68	66	64	61
	20	82	79	78	77	75	72	70	68	66	65	64	61
	30	73	71	70	70	68	66	64	63	61	60	60	58
	40	65	65	65	64	63	61	60	59	57	57	56	55
	50	59	59	59	59	58	57	56	55	54	53	53	52
	60	55	55	55	55	55	54	53	52	51	51	50	49
	70	51	51	51	51	51	51	51	50	49	48	48	48
	80	48	48	48	48	48	48	48	48	48	46	46	45
	90	45	45	45	45	45	45	45	45	45	45	44	44
Zone 3	0	106	100	97	94	88	83	77	72	68	66	64	61
	10	94	91	89	87	84	81	77	72	68	66	64	61
	20	82	79	78	77	75	72	70	68	66	65	64	61
	30	73	71	70	70	68	66	64	63	61	60	60	58
	40	65	65	65	64	63	61	60	59	57	57	56	55
	50	59	59	59	59	58	57	56	55	54	53	53	52
	60	55	55	55	55	55	54	53	52	51	51	50	49
	70	51	51	51	51	51	51	51	50	49	48	48	48
	80	48	48	48	48	48	48	48	48	48	46	46	45
	90	45	45	45	45	45	45	45	45	45	45	44	44

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

Table 6 Mean Roof Height: $0 < h \leq 15$ ft Panel Orientation: Portrait
 Roof Angle: $27 < \theta \leq 45$ degrees
 Exposure Category: D

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)										
		100	110	115	120	130	140	150	160	170	175	180
Zone 1	0	99	93	90	87	82	78	73	70	66	64	63
	10	91	87	85	83	80	77	73	70	66	64	63
	20	79	77	75	74	72	69	67	65	63	61	60
	30	71	69	68	68	66	64	62	60	58	58	57
	40	65	64	63	62	61	59	58	56	55	54	52
	50	59	59	59	58	57	56	55	53	52	51	50
	60	55	55	55	55	54	53	52	51	50	49	49
	70	51	51	51	51	51	50	49	48	48	48	46
	80	48	48	48	48	48	48	48	46	45	45	44
	90	45	45	45	45	45	45	45	45	44	43	42
Zone 2	0	99	93	90	87	81	75	70	66	62	60	58
	10	91	87	85	83	80	75	70	66	62	60	58
	20	79	77	75	74	72	69	67	65	62	60	58
	30	71	69	68	68	66	64	62	60	58	58	55
	40	65	64	63	62	61	59	58	56	55	54	52
	50	59	59	59	58	57	56	55	53	52	51	50
	60	55	55	55	55	54	53	52	51	50	49	48
	70	51	51	51	51	51	50	49	48	48	48	46
	80	48	48	48	48	48	48	48	46	45	45	44
	90	45	45	45	45	45	45	45	45	44	43	42
Zone 3	0	99	93	90	87	81	75	70	66	62	60	58
	10	91	87	85	83	80	75	70	66	62	60	58
	20	79	77	75	74	72	69	67	65	62	60	58
	30	71	69	68	68	66	64	62	60	58	58	55
	40	65	64	63	62	61	59	58	56	55	54	52
	50	59	59	59	58	57	56	55	53	52	51	50
	60	55	55	55	55	54	53	52	51	50	49	48
	70	51	51	51	51	51	50	49	48	48	48	46
	80	48	48	48	48	48	48	48	46	45	45	44
	90	45	45	45	45	45	45	45	45	44	43	42

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System
Table 7

 Mean Roof Height: $0 < h \leq 15$ ft

Panel Orientation: Landscape

 Roof Angle: $0 < \theta \leq 7$ degrees

Exposure Category: C

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)										
		100	110	115	120	130	140	150	160	170	175	180
Zone 1	0	121	121	121	121	121	121	112	105	98	95	92
	10	120	120	119	119	117	116	112	105	98	95	92
	20	101	101	101	101	101	101	101	101	98	95	92
	30	90	90	90	90	90	90	90	90	90	90	87
	40	82	82	82	82	82	82	82	82	82	82	82
	50	74	74	74	74	74	74	74	74	74	74	74
	60	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	121	114	109	104	95	88	82	77	72	70	68
	10	120	114	109	104	95	88	82	77	72	70	68
	20	101	101	101	101	95	88	82	77	72	70	68
	30	90	90	90	90	90	88	82	77	72	70	68
	40	82	82	82	82	82	82	82	77	72	70	68
	50	74	74	74	74	74	74	74	74	72	70	68
	60	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56
Zone 3	0	100	90	86	82	76	70	65	61	57	55	54
	10	100	90	86	82	76	70	65	61	57	55	54
	20	100	90	86	82	76	70	65	61	57	55	54
	30	90	90	86	82	76	70	65	61	57	55	54
	40	82	82	82	82	76	70	65	61	57	55	54
	50	74	74	74	74	74	70	65	61	57	55	54
	60	68	68	68	68	68	68	65	61	57	55	54
	70	64	64	64	64	64	64	64	61	57	55	54
	80	60	60	60	60	60	60	60	60	57	55	54
	90	56	56	56	56	56	56	56	56	55	54	51

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

Table 8 Mean Roof Height: $0 < h \leq 15$ ft Panel Orientation: Landscape
 Roof Angle: $0 < \theta \leq 7$ degrees
 Exposure Category: D

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)										
		100	110	115	120	130	140	150	160	170	175	180
Zone 1	0	121	121	121	121	118	109	101	94	89	86	83
	10	120	119	118	117	116	109	101	94	89	86	83
	20	101	101	101	101	101	101	100	94	89	86	83
	30	90	90	90	90	90	90	90	90	89	86	83
	40	82	82	82	82	82	82	82	82	82	82	79
	50	74	74	74	74	74	74	74	74	74	74	74
	60	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	114	103	98	94	86	80	74	69	65	63	61
	10	114	103	98	94	86	80	74	69	65	63	61
	20	101	101	98	94	86	80	74	69	65	63	61
	30	90	90	90	90	86	80	74	69	65	63	61
	40	82	82	82	82	82	80	74	69	65	63	61
	50	74	74	74	74	74	74	74	69	65	63	61
	60	68	68	68	68	68	68	68	68	65	63	61
	70	64	64	64	64	64	64	64	64	63	61	58
	80	60	60	60	60	60	60	60	60	60	60	58
	90	56	56	56	56	56	56	56	56	56	56	56
Zone 3	0	90	81	78	74	68	63	59	55	52	50	49
	10	90	81	78	74	68	63	59	55	52	50	49
	20	90	81	78	74	68	63	59	55	52	50	49
	30	90	81	78	74	68	63	59	55	52	50	49
	40	82	81	78	74	68	63	59	55	52	50	49
	50	74	74	74	74	68	63	59	55	52	50	49
	60	68	68	68	68	68	63	59	55	52	50	49
	70	64	64	64	64	64	63	59	55	52	50	49
	80	60	60	60	60	60	60	59	55	52	50	49
	90	56	56	56	56	56	56	56	55	52	50	49

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

Table 9 Mean Roof Height: $0 < h \leq 15$ ft Panel Orientation: Landscape
 Roof Angle: $7 < \theta \leq 27$ degrees
 Exposure Category: C

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)										
		100	110	115	120	130	140	150	160	170	175	180
Zone 1	0	121	121	121	121	121	121	116	108	102	99	96
	10	119	117	116	115	113	111	109	107	102	99	96
	20	101	101	101	101	99	97	95	93	91	90	90
	30	86	86	86	86	86	86	85	83	82	81	81
	40	75	75	75	75	75	75	75	75	74	74	73
	50	68	68	68	68	68	68	68	68	68	68	68
	60	63	63	63	63	63	63	63	63	63	63	63
	70	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52
Zone 2	0	121	115	110	105	97	89	83	78	73	71	69
	10	119	115	110	105	97	89	83	78	73	71	69
	20	101	101	101	101	97	89	83	78	73	71	69
	30	86	86	86	86	86	86	83	78	73	71	69
	40	75	75	75	75	75	75	75	75	73	71	69
	50	68	68	68	68	68	68	68	68	68	68	68
	60	63	63	63	63	63	63	63	63	63	63	63
	70	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52
Zone 3	0	102	92	88	84	78	72	67	63	59	57	56
	10	102	92	88	84	78	72	67	63	59	57	56
	20	101	92	88	84	78	72	67	63	59	57	56
	30	86	86	86	84	78	72	67	63	59	57	56
	40	75	75	75	75	75	72	67	63	59	57	56
	50	68	68	68	68	68	68	67	63	59	57	56
	60	63	63	63	63	63	63	63	63	59	57	56
	70	58	58	58	58	58	58	58	58	58	57	56
	80	55	55	55	55	55	55	55	55	55	55	53
	90	52	52	52	52	52	52	52	52	52	52	52

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 15$ ft							Panel Orientation: Landscape				
Table 10		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	121	113	105	98	92	89	87	82
	10	117	115	114	113	111	108	105	98	92	89	87	82
	20	101	100	99	98	96	94	92	90	88	87	86	82
	30	86	86	86	86	85	84	83	81	80	79	78	77
	40	75	75	75	75	75	75	75	74	73	72	72	71
	50	68	68	68	68	68	68	68	68	68	67	67	66
	60	63	63	63	63	63	63	63	63	63	63	63	62
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 2	0	115	104	99	95	87	81	75	71	66	64	63	59
	10	115	104	99	95	87	81	75	71	66	64	63	59
	20	101	100	99	95	87	81	75	71	66	64	63	59
	30	86	86	86	86	85	81	75	71	66	64	63	59
	40	75	75	75	75	75	75	75	71	66	64	63	59
	50	68	68	68	68	68	68	68	68	66	64	63	59
	60	63	63	63	63	63	63	63	63	63	63	63	59
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 3	0	92	83	80	76	70	65	61	57	53	52	50	48
	10	92	83	80	76	70	65	61	57	53	52	50	48
	20	92	83	80	76	70	65	61	57	53	52	50	48
	30	86	83	80	76	70	65	61	57	53	52	50	48
	40	75	75	75	75	70	65	61	57	53	52	50	48
	50	68	68	68	68	68	65	61	57	53	52	50	48
	60	63	63	63	63	63	63	61	57	53	52	50	48
	70	58	58	58	58	58	58	58	57	53	52	50	48
	80	55	55	55	55	55	55	55	55	53	52	50	48
	90	52	52	52	52	52	52	52	52	52	52	50	48

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 15$ ft							Panel Orientation: Landscape				
Table 11		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	119	116	112	106	101	96	91	89	87	83
	10	119	115	113	111	107	103	99	95	91	89	87	83
	20	104	101	99	98	95	92	89	86	84	82	81	79
	30	93	91	89	88	86	84	82	80	78	77	76	74
	40	83	83	82	81	80	78	76	74	73	72	71	69
	50	75	75	75	75	74	73	71	70	69	68	67	66
	60	69	69	69	69	69	69	68	66	65	64	64	63
	70	65	65	65	65	65	65	64	63	62	62	61	60
	80	61	61	61	61	61	61	61	60	59	59	58	58
	90	58	58	58	58	58	58	58	58	57	57	56	55
Zone 2	0	121	121	119	116	112	105	98	92	86	84	82	77
	10	119	115	113	111	107	103	98	92	86	84	82	77
	20	104	101	99	98	95	92	89	86	84	82	81	77
	30	93	91	89	88	86	84	82	80	78	77	76	74
	40	83	83	82	81	80	78	76	74	73	72	71	69
	50	75	75	75	75	74	73	71	70	69	68	67	66
	60	69	69	69	69	69	69	68	66	65	64	64	63
	70	65	65	65	65	65	65	64	63	62	62	61	60
	80	61	61	61	61	61	61	61	60	59	59	58	58
	90	58	58	58	58	58	58	58	58	57	57	56	55
Zone 3	0	121	121	119	116	112	105	98	92	86	84	82	77
	10	119	115	113	111	107	103	98	92	86	84	82	77
	20	104	101	99	98	95	92	89	86	84	82	81	77
	30	93	91	89	88	86	84	82	80	78	77	76	74
	40	83	83	82	81	80	78	76	74	73	72	71	69
	50	75	75	75	75	74	73	71	70	69	68	67	66
	60	69	69	69	69	69	69	68	66	65	64	64	63
	70	65	65	65	65	65	65	64	63	62	62	61	60
	80	61	61	61	61	61	61	61	60	59	59	58	58
	90	58	58	58	58	58	58	58	58	57	57	56	55

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 15$ ft							Panel Orientation: Landscape				
Table 12		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	116	113	111	104	98	93	88	84	82	80	76
	10	115	110	108	106	101	97	93	88	84	82	80	76
	20	101	97	96	94	91	88	85	82	79	78	77	74
	30	91	88	87	86	83	81	79	76	74	73	72	70
	40	83	81	80	79	77	75	74	72	70	69	68	66
	50	75	75	75	74	72	71	69	68	66	65	65	63
	60	69	69	69	69	68	67	66	64	63	62	62	60
	70	65	65	65	65	65	64	63	61	60	60	59	58
	80	61	61	61	61	61	61	60	59	58	57	57	56
	90	58	58	58	58	58	58	58	57	56	55	55	54
Zone 2	0	121	116	113	111	102	95	89	83	78	76	74	70
	10	115	110	108	106	101	95	89	83	78	76	74	70
	20	101	97	96	94	91	88	85	82	78	76	74	70
	30	91	88	87	86	83	81	79	76	74	73	72	70
	40	83	81	80	79	77	75	74	72	70	69	68	66
	50	75	75	75	74	72	71	69	68	66	65	65	63
	60	69	69	69	69	68	67	66	64	63	62	62	60
	70	65	65	65	65	65	64	63	61	60	60	59	58
	80	61	61	61	61	61	61	60	59	58	57	57	56
	90	58	58	58	58	58	58	58	57	56	55	55	54
Zone 3	0	121	116	113	111	102	95	89	83	78	76	74	70
	10	115	110	108	106	101	95	89	83	78	76	74	70
	20	101	97	96	94	91	88	85	82	78	76	74	70
	30	91	88	87	86	83	81	79	76	74	73	72	70
	40	83	81	80	79	77	75	74	72	70	69	68	66
	50	75	75	75	74	72	71	69	68	66	65	65	63
	60	69	69	69	69	68	67	66	64	63	62	62	60
	70	65	65	65	65	65	64	63	61	60	60	59	58
	80	61	61	61	61	61	61	60	59	58	57	57	56
	90	58	58	58	58	58	58	58	57	56	55	55	54

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Portrait				
Table 13		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	116	116	116	116	106	99	92	86	83	81	76
	10	102	102	102	102	102	101	99	92	86	83	81	76
	20	86	86	86	86	86	86	86	86	85	83	81	76
	30	74	74	74	74	74	74	74	74	74	74	74	73
	40	65	65	65	65	65	65	65	65	65	65	65	65
	50	59	59	59	59	59	59	59	59	59	59	59	59
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	112	100	95	91	83	77	72	67	63	61	59	56
	10	102	100	95	91	83	77	72	67	63	61	59	56
	20	86	86	86	86	83	77	72	67	63	61	59	56
	30	74	74	74	74	74	74	72	67	63	61	59	56
	40	65	65	65	65	65	65	65	65	63	61	59	56
	50	59	59	59	59	59	59	59	59	59	59	59	56
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 3	0	87	79	75	72	66	61	57	53	50	48	48	44
	10	87	79	75	72	66	61	57	53	50	48	48	44
	20	86	79	75	72	66	61	57	53	50	48	48	44
	30	74	74	74	72	66	61	57	53	50	48	48	44
	40	65	65	65	65	65	61	57	53	50	48	48	44
	50	59	59	59	59	59	59	57	53	50	48	48	44
	60	54	54	54	54	54	54	54	53	50	48	48	44
	70	50	50	50	50	50	50	50	50	50	48	48	44
	80	48	48	48	48	48	48	48	48	48	48	48	44
	90	44	44	44	44	44	44	44	44	44	44	44	44

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

 Mean Roof Height: $15 < h \leq 30$ ft Panel Orientation: Portrait

Table 14 Roof Angle: $0 < \theta \leq 7$ degrees Exposure Category: C

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	116	110	105	96	88	82	76	72	69	67	64
	10	102	102	101	100	96	88	82	76	72	69	67	64
	20	86	86	86	86	86	86	82	76	72	69	67	64
	30	74	74	74	74	74	74	74	73	72	69	67	64
	40	65	65	65	65	65	65	65	65	65	65	65	64
	50	59	59	59	59	59	59	59	59	59	59	59	59
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	93	83	79	76	70	64	60	56	53	51	50	48
	10	93	83	79	76	70	64	60	56	53	51	50	48
	20	86	83	79	76	70	64	60	56	53	51	50	48
	30	74	74	74	74	70	64	60	56	53	51	50	48
	40	65	65	65	65	65	64	60	56	53	51	50	48
	50	59	59	59	59	59	59	59	56	53	51	50	48
	60	54	54	54	54	54	54	54	54	53	51	50	48
	70	50	50	50	50	50	50	50	50	50	50	50	48
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 3	0	73	66	63	60	55	51	48	45	42	41	39	37
	10	73	66	63	60	55	51	48	45	42	41	39	37
	20	73	66	63	60	55	51	48	45	42	41	39	37
	30	73	66	63	60	55	51	48	45	42	41	39	37
	40	65	65	63	60	55	51	48	45	42	41	39	37
	50	59	59	59	59	55	51	48	45	42	41	39	37
	60	54	54	54	54	54	51	48	45	42	41	39	37
	70	50	50	50	50	50	50	48	45	42	41	39	37
	80	48	48	48	48	48	48	48	45	42	41	39	37
	90	44	44	44	44	44	44	44	44	42	41	39	37

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

 Mean Roof Height: $15 < h \leq 30$ ft Panel Orientation: Portrait

Table 15
 Roof Angle: $0 < \theta \leq 7$ degrees
 Exposure Category: D

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	
Zone 1	0	116	105	100	95	87	81	75	70	65	63	62	58
	10	102	100	100	95	87	81	75	70	65	63	62	58
	20	86	86	86	86	85	81	75	70	65	63	62	58
	30	74	74	74	74	74	74	73	70	65	63	62	58
	40	65	65	65	65	65	65	65	65	65	63	62	58
	50	59	59	59	59	59	59	59	59	59	59	59	58
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	84	76	73	69	64	59	55	51	48	48	45	43
	10	84	76	73	69	64	59	55	51	48	48	45	43
	20	84	76	73	69	64	59	55	51	48	48	45	43
	30	74	74	73	69	64	59	55	51	48	48	45	43
	40	65	65	65	65	64	59	55	51	48	48	45	43
	50	59	59	59	59	59	59	55	51	48	48	45	43
	60	54	54	54	54	54	54	54	51	48	48	45	43
	70	50	50	50	50	50	50	50	50	48	48	45	43
	80	48	48	48	48	48	48	48	48	48	48	45	43
	90	44	44	44	44	44	44	44	44	44	44	44	43
Zone 3	0	67	60	57	55	51	48	44	41	38	37	36	34
	10	67	60	57	55	51	48	44	41	38	37	36	34
	20	67	60	57	55	51	48	44	41	38	37	36	34
	30	67	60	57	55	51	48	44	41	38	37	36	34
	40	65	60	57	55	51	48	44	41	38	37	36	34
	50	59	59	57	55	51	48	44	41	38	37	36	34
	60	54	54	54	54	51	48	44	41	38	37	36	34
	70	50	50	50	50	50	48	44	41	38	37	36	34
	80	48	48	48	48	48	48	44	41	38	37	36	34
	90	44	44	44	44	44	44	44	41	38	37	36	34

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Portrait				
Table 16		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	116	116	116	113	109	101	94	89	86	83	79
	10	101	99	98	97	95	93	91	89	86	85	83	79
	20	80	80	80	80	80	78	77	76	74	74	73	72
	30	67	67	67	67	67	67	67	67	66	66	65	64
	40	59	59	59	59	59	59	59	59	59	59	59	59
	50	54	54	54	54	54	54	54	54	54	54	54	54
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	111	100	96	91	84	78	73	68	64	62	60	57
	10	101	99	96	91	84	78	73	68	64	62	60	57
	20	80	80	80	80	80	78	73	68	64	62	60	57
	30	67	67	67	67	67	67	67	67	64	62	60	57
	40	59	59	59	59	59	59	59	59	59	59	59	57
	50	54	54	54	54	54	54	54	54	54	54	54	54
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	89	80	77	73	68	63	58	55	51	50	48	46
	10	89	80	77	73	68	63	58	55	51	50	48	46
	20	80	80	77	73	68	63	58	55	51	50	48	46
	30	67	67	67	67	67	63	58	55	51	50	48	46
	40	59	59	59	59	59	59	58	55	51	50	48	46
	50	54	54	54	54	54	54	54	54	51	50	48	46
	60	49	49	49	49	49	49	49	49	49	49	48	46
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

 Mean Roof Height: $15 < h \leq 30$ ft Panel Orientation: Portrait

Table 17 Roof Angle: $7 < \theta \leq 27$ degrees Exposure Category: C

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	113	111	107	98	91	85	79	74	72	70	66
	10	98	95	94	92	90	87	85	79	74	72	70	66
	20	80	80	79	78	76	75	73	72	70	69	69	66
	30	67	67	67	67	67	67	65	64	63	63	62	61
	40	59	59	59	59	59	59	59	59	58	57	57	56
	50	54	54	54	54	54	54	54	54	54	53	53	52
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	93	84	80	77	71	65	61	57	54	52	51	48
	10	93	84	80	77	71	65	61	57	54	52	51	48
	20	80	80	79	77	71	65	61	57	54	52	51	48
	30	67	67	67	67	67	65	61	57	54	52	51	48
	40	59	59	59	59	59	59	59	57	54	52	51	48
	50	54	54	54	54	54	54	54	54	54	52	51	48
	60	49	49	49	49	49	49	49	49	49	49	49	48
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	74	67	64	62	57	53	49	46	43	42	41	39
	10	74	67	64	62	57	53	49	46	43	42	41	39
	20	74	67	64	62	57	53	49	46	43	42	41	39
	30	67	67	64	62	57	53	49	46	43	42	41	39
	40	59	59	59	59	57	53	49	46	43	42	41	39
	50	54	54	54	54	54	53	49	46	43	42	41	39
	60	49	49	49	49	49	49	49	46	43	42	41	39
	70	46	46	46	46	46	46	46	46	43	42	41	39
	80	43	43	43	43	43	43	43	43	43	42	41	39
	90	41	41	41	41	41	41	41	41	41	41	41	39

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft										Panel Orientation: Portrait	
Table 18		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	113	107	102	98	90	83	78	73	68	66	64	61
	10	95	93	91	90	87	83	78	73	68	66	64	61
	20	80	78	77	76	75	73	71	69	68	66	64	61
	30	67	67	67	67	66	65	64	63	61	61	60	59
	40	59	59	59	59	59	59	58	58	57	56	56	55
	50	54	54	54	54	54	54	54	53	53	52	52	51
	60	49	49	49	49	49	49	49	49	49	49	49	48
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	85	77	74	70	65	60	56	52	49	48	46	44
	10	85	77	74	70	65	60	56	52	49	48	46	44
	20	80	77	74	70	65	60	56	52	49	48	46	44
	30	67	67	67	67	65	60	56	52	49	48	46	44
	40	59	59	59	59	59	59	56	52	49	48	46	44
	50	54	54	54	54	54	54	54	52	49	48	46	44
	60	49	49	49	49	49	49	49	49	49	48	46	44
	70	46	46	46	46	46	46	46	46	46	46	46	44
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	68	62	59	57	52	48	45	42	40	38	37	35
	10	68	62	59	57	52	48	45	42	40	38	37	35
	20	68	62	59	57	52	48	45	42	40	38	37	35
	30	67	62	59	57	52	48	45	42	40	38	37	35
	40	59	59	59	57	52	48	45	42	40	38	37	35
	50	54	54	54	54	52	48	45	42	40	38	37	35
	60	49	49	49	49	49	48	45	42	40	38	37	35
	70	46	46	46	46	46	46	45	42	40	38	37	35
	80	43	43	43	43	43	43	43	42	40	38	37	35
	90	41	41	41	41	41	41	41	41	40	38	37	35

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft										Panel Orientation: Portrait		
Table 19		Roof Angle: $27 < \theta \leq 45$ degrees												
		Exposure Category: B												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	112	106	103	100	95	90	85	81	78	76	74	71	
	10	97	94	93	91	88	85	82	79	77	75	74	71	
	20	84	82	81	80	77	75	73	71	69	68	67	65	
	30	74	73	72	72	70	68	67	65	64	63	62	61	
	40	65	65	65	65	64	63	62	61	59	59	58	57	
	50	59	59	59	59	59	59	58	57	56	55	55	54	
	60	55	55	55	55	55	55	54	54	53	52	52	51	
	70	51	51	51	51	51	51	51	51	50	50	49	49	
	80	48	48	48	48	48	48	48	48	48	48	48	48	
	90	45	45	45	45	45	45	45	45	45	45	45	45	
Zone 2	0	112	106	103	100	95	90	85	80	75	73	71	67	
	10	97	94	93	91	88	85	82	79	75	73	71	67	
	20	84	82	81	80	77	75	73	71	69	68	67	65	
	30	74	73	72	72	70	68	67	65	64	63	62	61	
	40	65	65	65	65	64	63	62	61	59	59	58	57	
	50	59	59	59	59	59	59	58	57	56	55	55	54	
	60	55	55	55	55	55	55	54	54	53	52	52	51	
	70	51	51	51	51	51	51	51	51	50	50	49	49	
	80	48	48	48	48	48	48	48	48	48	48	48	48	
	90	45	45	45	45	45	45	45	45	45	45	45	45	
Zone 3	0	112	106	103	100	95	90	85	80	75	73	71	67	
	10	97	94	93	91	88	85	82	79	75	73	71	67	
	20	84	82	81	80	77	75	73	71	69	68	67	65	
	30	74	73	72	72	70	68	67	65	64	63	62	61	
	40	65	65	65	65	64	63	62	61	59	59	58	57	
	50	59	59	59	59	59	59	58	57	56	55	55	54	
	60	55	55	55	55	55	55	54	54	53	52	52	51	
	70	51	51	51	51	51	51	51	51	50	50	49	49	
	80	48	48	48	48	48	48	48	48	48	48	48	48	
	90	45	45	45	45	45	45	45	45	45	45	45	45	

Notes:

1. Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
2. Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft										Panel Orientation: Portrait	
Table 20		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	101	95	92	89	84	79	75	71	67	66	64	61
	10	92	88	86	84	81	78	75	71	67	66	64	61
	20	80	77	76	75	73	70	68	66	63	62	61	59
	30	72	70	69	68	66	64	63	61	59	58	57	56
	40	65	64	64	63	61	60	58	57	56	55	54	53
	50	59	59	59	59	57	56	55	54	53	52	51	50
	60	55	55	55	55	54	53	52	51	50	49	49	48
	70	51	51	51	51	51	50	50	49	48	48	48	46
	80	48	48	48	48	48	48	48	48	46	45	45	44
	90	45	45	45	45	45	45	45	45	44	44	43	43
Zone 2	0	101	95	92	89	83	77	72	67	63	61	60	57
	10	92	88	86	84	81	77	72	67	63	61	60	57
	20	80	77	76	75	73	70	68	66	63	61	60	57
	30	72	70	69	68	66	64	63	61	59	58	57	56
	40	65	64	64	63	61	60	58	57	56	55	54	53
	50	59	59	59	59	57	56	55	54	53	52	51	50
	60	55	55	55	55	54	53	52	51	50	49	49	48
	70	51	51	51	51	51	50	50	49	48	48	48	46
	80	48	48	48	48	48	48	48	48	46	45	45	44
	90	45	45	45	45	45	45	45	45	44	44	43	43
Zone 3	0	101	95	92	89	83	77	72	67	63	61	60	57
	10	92	88	86	84	81	77	72	67	63	61	60	57
	20	80	77	76	75	73	70	68	66	63	61	60	57
	30	72	70	69	68	66	64	63	61	59	58	57	56
	40	65	64	64	63	61	60	58	57	56	55	54	53
	50	59	59	59	59	57	56	55	54	53	52	51	50
	60	55	55	55	55	54	53	52	51	50	49	49	48
	70	51	51	51	51	51	50	50	49	48	48	48	46
	80	48	48	48	48	48	48	48	48	46	45	45	44
	90	45	45	45	45	45	45	45	45	44	44	43	43

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft										Panel Orientation: Portrait		
Table 21		Roof Angle: $27 < \theta \leq 45$ degrees												
		Exposure Category: D												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	96	89	86	84	78	74	70	66	63	61	60	57	
	10	88	85	83	81	77	74	70	66	63	61	60	57	
	20	78	75	74	72	70	67	65	63	60	59	58	56	
	30	70	68	67	66	64	62	60	58	57	56	55	53	
	40	64	63	62	61	60	58	57	55	53	53	52	51	
	50	59	59	58	57	56	55	53	52	51	50	49	48	
	60	55	55	55	54	53	52	51	50	48	48	48	46	
	70	51	51	51	51	50	49	48	48	46	46	45	44	
	80	48	48	48	48	48	48	46	46	45	44	44	43	
	90	45	45	45	45	45	45	45	44	43	43	42	41	
Zone 2	0	96	89	86	82	76	71	66	62	58	56	55	52	
	10	88	85	83	81	76	71	66	62	58	56	55	52	
	20	78	75	74	72	70	67	65	62	58	56	55	52	
	30	70	68	67	66	64	62	60	58	57	56	55	52	
	40	64	63	62	61	60	58	57	55	53	53	52	51	
	50	59	59	58	57	56	55	53	52	51	50	49	48	
	60	55	55	55	54	53	52	51	50	48	48	48	46	
	70	51	51	51	51	50	49	48	48	46	46	45	44	
	80	48	48	48	48	48	48	46	46	45	44	44	43	
	90	45	45	45	45	45	45	45	44	43	43	42	41	
Zone 3	0	96	89	86	82	76	71	66	62	58	56	55	52	
	10	88	85	83	81	76	71	66	62	58	56	55	52	
	20	78	75	74	72	70	67	65	62	58	56	55	52	
	30	70	68	67	66	64	62	60	58	57	56	55	52	
	40	64	63	62	61	60	58	57	55	53	53	52	51	
	50	59	59	58	57	56	55	53	52	51	50	49	48	
	60	55	55	55	54	53	52	51	50	48	48	48	46	
	70	51	51	51	51	50	49	48	48	46	46	45	44	
	80	48	48	48	48	48	48	46	46	45	44	44	43	
	90	45	45	45	45	45	45	45	44	43	43	42	41	

Notes:

1. Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
2. Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Landscape				
Table 22		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	121	121	121	116	109	106	102	97
	10	120	120	120	120	119	118	117	115	109	106	102	97
	20	101	101	101	101	101	101	101	101	101	101	100	97
	30	90	90	90	90	90	90	90	90	90	90	90	90
	40	82	82	82	82	82	82	82	82	82	82	82	82
	50	74	74	74	74	74	74	74	74	74	74	74	74
	60	68	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	121	121	121	116	106	98	91	85	80	77	75	71
	10	120	120	120	116	106	98	91	85	80	77	75	71
	20	101	101	101	101	101	98	91	85	80	77	75	71
	30	90	90	90	90	90	90	90	85	80	77	75	71
	40	82	82	82	82	82	82	82	82	80	77	75	71
	50	74	74	74	74	74	74	74	74	74	74	74	71
	60	68	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 3	0	111	100	95	91	84	77	72	67	63	61	60	56
	10	111	100	95	91	84	77	72	67	63	61	60	56
	20	101	100	95	91	84	77	72	67	63	61	60	56
	30	90	90	90	90	84	77	72	67	63	61	60	56
	40	82	82	82	82	82	77	72	67	63	61	60	56
	50	74	74	74	74	74	74	72	67	63	61	60	56
	60	68	68	68	68	68	68	68	67	63	61	60	56
	70	64	64	64	64	64	64	64	64	63	61	60	56
	80	60	60	60	60	60	60	60	60	60	60	60	56
	90	56	56	56	56	56	56	56	56	56	56	56	56

Notes:

1. Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
2. Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft										Panel Orientation: Landscape	
		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	121	112	104	97	91	88	86	81
	10	120	119	118	118	116	112	104	97	91	88	86	81
	20	101	101	101	101	101	101	100	97	91	88	86	81
	30	90	90	90	90	90	90	90	90	90	88	86	81
	40	82	82	82	82	82	82	82	82	82	82	82	81
	50	74	74	74	74	74	74	74	74	74	74	74	74
	60	68	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	117	106	101	96	88	82	76	71	67	65	63	59
	10	117	106	101	96	88	82	76	71	67	65	63	59
	20	101	101	101	96	88	82	76	71	67	65	63	59
	30	90	90	90	90	88	82	76	71	67	65	63	59
	40	82	82	82	82	82	82	76	71	67	65	63	59
	50	74	74	74	74	74	74	74	71	67	65	63	59
	60	68	68	68	68	68	68	68	68	67	65	63	59
	70	64	64	64	64	64	64	64	64	64	64	63	59
	80	60	60	60	60	60	60	60	60	60	60	60	59
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 3	0	92	84	80	76	70	65	60	57	53	52	50	48
	10	92	84	80	76	70	65	60	57	53	52	50	48
	20	92	84	80	76	70	65	60	57	53	52	50	48
	30	90	84	80	76	70	65	60	57	53	52	50	48
	40	82	82	80	76	70	65	60	57	53	52	50	48
	50	74	74	74	74	70	65	60	57	53	52	50	48
	60	68	68	68	68	68	65	60	57	53	52	50	48
	70	64	64	64	64	64	64	60	57	53	52	50	48
	80	60	60	60	60	60	60	60	57	53	52	50	48
	90	56	56	56	56	56	56	56	56	53	52	50	48

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft										Panel Orientation: Landscape	
		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	111	102	95	89	83	81	78	74
	10	119	118	117	116	111	102	95	89	83	81	78	74
	20	101	101	101	101	101	100	95	89	83	81	78	74
	30	90	90	90	90	90	90	90	89	83	81	78	74
	40	82	82	82	82	82	82	82	82	82	81	78	74
	50	74	74	74	74	74	74	74	74	74	74	74	74
	60	68	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	107	97	92	88	81	75	70	65	61	59	58	55
	10	107	97	92	88	81	75	70	65	61	59	58	55
	20	101	97	92	88	81	75	70	65	61	59	58	55
	30	90	90	90	88	81	75	70	65	61	59	58	55
	40	82	82	82	82	81	75	70	65	61	59	58	55
	50	74	74	74	74	74	74	70	65	61	59	58	55
	60	68	68	68	68	68	68	68	65	61	59	58	55
	70	64	64	64	64	64	64	64	64	61	59	58	55
	80	60	60	60	60	60	60	60	60	60	59	58	55
	90	56	56	56	56	56	56	56	56	56	56	56	55
Zone 3	0	85	76	73	70	64	59	55	52	49	48	46	43
	10	85	76	73	70	64	59	55	52	49	48	46	43
	20	85	76	73	70	64	59	55	52	49	48	46	43
	30	85	76	73	70	64	59	55	52	49	48	46	43
	40	82	76	73	70	64	59	55	52	49	48	46	43
	50	74	74	73	70	64	59	55	52	49	48	46	43
	60	68	68	68	68	64	59	55	52	49	48	46	43
	70	64	64	64	64	64	59	55	52	49	48	46	43
	80	60	60	60	60	60	59	55	52	49	48	46	43
	90	56	56	56	56	56	56	55	52	49	48	46	43

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Landscape				
Table 25		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	121	121	121	120	112	109	106	100
	10	120	119	118	117	115	114	112	110	108	108	106	100
	20	101	101	101	101	101	99	98	96	94	93	93	91
	30	86	86	86	86	86	86	86	85	84	83	83	82
	40	75	75	75	75	75	75	75	75	75	75	75	75
	50	68	68	68	68	68	68	68	68	68	68	68	68
	60	63	63	63	63	63	63	63	63	63	63	63	63
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 2	0	121	121	121	116	107	99	92	86	81	79	76	72
	10	120	119	118	116	107	99	92	86	81	79	76	72
	20	101	101	101	101	101	99	92	86	81	79	76	72
	30	86	86	86	86	86	86	86	85	81	79	76	72
	40	75	75	75	75	75	75	75	75	75	75	75	72
	50	68	68	68	68	68	68	68	68	68	68	68	68
	60	63	63	63	63	63	63	63	63	63	63	63	63
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 3	0	112	102	97	93	86	79	74	69	65	63	61	58
	10	112	102	97	93	86	79	74	69	65	63	61	58
	20	101	101	97	93	86	79	74	69	65	63	61	58
	30	86	86	86	86	86	79	74	69	65	63	61	58
	40	75	75	75	75	75	75	74	69	65	63	61	58
	50	68	68	68	68	68	68	68	68	65	63	61	58
	60	63	63	63	63	63	63	63	63	63	63	61	58
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52

Notes:

1. Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
2. Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft										Panel Orientation: Landscape		
		Roof Angle: $7 < \theta \leq 27$ degrees												
		Exposure Category: C												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	121	121	121	121	121	116	108	101	94	92	89	84	
	10	117	115	114	113	111	109	107	101	94	92	89	84	
	20	101	101	100	99	97	95	93	91	89	88	87	84	
	30	86	86	86	86	86	85	83	82	80	79	79	77	
	40	75	75	75	75	75	75	75	75	74	73	72	71	
	50	68	68	68	68	68	68	68	68	68	68	67	66	
	60	63	63	63	63	63	63	63	63	63	63	63	62	
	70	58	58	58	58	58	58	58	58	58	58	58	58	
	80	55	55	55	55	55	55	55	55	55	55	55	55	
	90	52	52	52	52	52	52	52	52	52	52	52	52	
Zone 2	0	118	107	102	97	90	83	77	72	68	66	64	61	
	10	117	107	102	97	90	83	77	72	68	66	64	61	
	20	101	101	100	97	90	83	77	72	68	66	64	61	
	30	86	86	86	86	86	83	77	72	68	66	64	61	
	40	75	75	75	75	75	75	75	72	68	66	64	61	
	50	68	68	68	68	68	68	68	68	68	66	64	61	
	60	63	63	63	63	63	63	63	63	63	63	63	61	
	70	58	58	58	58	58	58	58	58	58	58	58	58	
	80	55	55	55	55	55	55	55	55	55	55	55	55	
	90	52	52	52	52	52	52	52	52	52	52	52	52	
Zone 3	0	94	86	82	78	72	67	62	58	55	53	52	49	
	10	94	86	82	78	72	67	62	58	55	53	52	49	
	20	94	86	82	78	72	67	62	58	55	53	52	49	
	30	86	86	82	78	72	67	62	58	55	53	52	49	
	40	75	75	75	75	72	67	62	58	55	53	52	49	
	50	68	68	68	68	68	67	62	58	55	53	52	49	
	60	63	63	63	63	63	63	62	58	55	53	52	49	
	70	58	58	58	58	58	58	58	58	55	53	52	49	
	80	55	55	55	55	55	55	55	55	55	53	52	49	
	90	52	52	52	52	52	52	52	52	52	52	52	52	

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft										Panel Orientation: Landscape	
		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	114	106	98	92	87	84	82	77
	10	116	113	112	111	109	106	98	92	87	84	82	77
	20	101	99	98	97	95	93	90	88	86	84	82	77
	30	86	86	86	86	84	83	81	80	78	77	76	75
	40	75	75	75	75	75	75	74	73	72	71	71	69
	50	68	68	68	68	68	68	68	68	67	66	66	65
	60	63	63	63	63	63	63	63	63	63	62	62	61
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 2	0	108	98	93	89	82	76	71	66	63	61	59	56
	10	108	98	93	89	82	76	71	66	63	61	59	56
	20	101	98	93	89	82	76	71	66	63	61	59	56
	30	86	86	86	86	82	76	71	66	63	61	59	56
	40	75	75	75	75	75	75	71	66	63	61	59	56
	50	68	68	68	68	68	68	68	66	63	61	59	56
	60	63	63	63	63	63	63	63	63	63	61	59	56
	70	58	58	58	58	58	58	58	58	58	58	58	56
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 3	0	87	79	75	72	66	61	57	54	50	49	48	45
	10	87	79	75	72	66	61	57	54	50	49	48	45
	20	87	79	75	72	66	61	57	54	50	49	48	45
	30	86	79	75	72	66	61	57	54	50	49	48	45
	40	75	75	75	72	66	61	57	54	50	49	48	45
	50	68	68	68	68	66	61	57	54	50	49	48	45
	60	63	63	63	63	63	61	57	54	50	49	48	45
	70	58	58	58	58	58	58	57	54	50	49	48	45
	80	55	55	55	55	55	55	55	54	50	49	48	45
	90	52	52	52	52	52	52	52	52	50	49	48	45

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Landscape				
Table 28		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	117	113	108	103	98	96	94	90
	10	121	119	118	116	112	108	104	101	97	96	94	90
	20	106	104	102	101	98	96	93	91	88	87	86	83
	30	94	93	92	91	89	87	85	83	81	80	79	77
	40	83	83	83	83	82	80	79	77	75	75	74	72
	50	75	75	75	75	75	75	73	72	71	70	70	68
	60	69	69	69	69	69	69	69	68	67	66	66	65
	70	65	65	65	65	65	65	65	65	64	63	63	62
	80	61	61	61	61	61	61	61	61	61	60	60	59
	90	58	58	58	58	58	58	58	58	58	58	58	57
Zone 2	0	121	121	121	121	117	113	108	101	95	92	90	85
	10	121	119	118	116	112	108	104	101	95	92	90	85
	20	106	104	102	101	98	96	93	91	88	87	86	83
	30	94	93	92	91	89	87	85	83	81	80	79	77
	40	83	83	83	83	82	80	79	77	75	75	74	72
	50	75	75	75	75	75	75	73	72	71	70	70	68
	60	69	69	69	69	69	69	69	68	67	66	66	65
	70	65	65	65	65	65	65	65	65	64	63	63	62
	80	61	61	61	61	61	61	61	61	61	60	60	59
	90	58	58	58	58	58	58	58	58	58	58	58	57
Zone 3	0	121	121	121	121	117	113	108	101	95	92	90	85
	10	121	119	118	116	112	108	104	101	95	92	90	85
	20	106	104	102	101	98	96	93	91	88	87	86	83
	30	94	93	92	91	89	87	85	83	81	80	79	77
	40	83	83	83	83	82	80	79	77	75	75	74	72
	50	75	75	75	75	75	75	73	72	71	70	70	68
	60	69	69	69	69	69	69	69	68	67	66	66	65
	70	65	65	65	65	65	65	65	65	64	63	63	62
	80	61	61	61	61	61	61	61	61	61	60	60	59
	90	58	58	58	58	58	58	58	58	58	58	58	57

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $15 < h \leq 30$ ft							Panel Orientation: Landscape				
Table 29		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	117	115	112	106	100	95	90	86	84	82	78
	10	116	112	109	107	103	99	95	90	86	84	82	78
	20	101	98	97	95	92	89	86	83	81	79	78	75
	30	91	89	88	86	84	82	80	77	75	74	73	71
	40	83	82	81	80	78	76	74	72	71	70	69	67
	50	75	75	75	74	73	71	70	68	67	66	65	64
	60	69	69	69	69	69	67	66	65	64	63	62	61
	70	65	65	65	65	65	64	63	62	61	60	60	58
	80	61	61	61	61	61	61	60	59	58	58	57	56
	90	58	58	58	58	58	58	58	57	56	56	55	54
Zone 2	0	121	117	115	112	105	98	91	85	80	78	76	72
	10	116	112	109	107	103	98	91	85	80	78	76	72
	20	101	98	97	95	92	89	86	83	80	78	76	72
	30	91	89	88	86	84	82	80	77	75	74	73	71
	40	83	82	81	80	78	76	74	72	71	70	69	67
	50	75	75	75	74	73	71	70	68	67	66	65	64
	60	69	69	69	69	69	67	66	65	64	63	62	61
	70	65	65	65	65	65	64	63	62	61	60	60	58
	80	61	61	61	61	61	61	60	59	58	58	57	56
	90	58	58	58	58	58	58	58	57	56	56	55	54
Zone 3	0	121	117	115	112	105	98	91	85	80	78	76	72
	10	116	112	109	107	103	98	91	85	80	78	76	72
	20	101	98	97	95	92	89	86	83	80	78	76	72
	30	91	89	88	86	84	82	80	77	75	74	73	71
	40	83	82	81	80	78	76	74	72	71	70	69	67
	50	75	75	75	74	73	71	70	68	67	66	65	64
	60	69	69	69	69	69	67	66	65	64	63	62	61
	70	65	65	65	65	65	64	63	62	61	60	60	58
	80	61	61	61	61	61	61	60	59	58	58	57	56
	90	58	58	58	58	58	58	58	57	56	56	55	54

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

Table 30	Mean Roof Height: $15 < h \leq 30$ ft							Panel Orientation: Landscape				
	Roof Angle: $27 < \theta \leq 45$ degrees											
	Exposure Category: D											

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	
Zone 1	0	118	112	110	106	100	94	89	84	80	78	76	72
	10	112	107	105	103	98	94	89	84	80	78	76	72
	20	99	95	94	92	89	85	82	79	77	75	74	71
	30	89	87	85	84	81	79	77	74	72	71	70	68
	40	82	80	79	78	76	74	72	70	68	67	66	64
	50	75	74	74	73	71	70	68	66	65	64	63	61
	60	69	69	69	69	67	66	64	63	62	61	60	59
	70	65	65	65	65	64	63	62	60	59	58	58	57
	80	61	61	61	61	61	60	59	58	57	56	56	54
	90	58	58	58	58	58	58	57	56	55	54	54	53
Zone 2	0	118	112	109	105	97	90	84	78	74	72	70	66
	10	112	107	105	103	97	90	84	78	74	72	70	66
	20	99	95	94	92	89	85	82	78	74	72	70	66
	30	89	87	85	84	81	79	77	74	72	71	70	66
	40	82	80	79	78	76	74	72	70	68	67	66	64
	50	75	74	74	73	71	70	68	66	65	64	63	61
	60	69	69	69	69	67	66	64	63	62	61	60	59
	70	65	65	65	65	64	63	62	60	59	58	58	57
	80	61	61	61	61	61	60	59	58	57	56	56	54
	90	58	58	58	58	58	58	57	56	55	54	54	53
Zone 3	0	118	112	109	105	97	90	84	78	74	72	70	66
	10	112	107	105	103	97	90	84	78	74	72	70	66
	20	99	95	94	92	89	85	82	78	74	72	70	66
	30	89	87	85	84	81	79	77	74	72	71	70	66
	40	82	80	79	78	76	74	72	70	68	67	66	64
	50	75	74	74	73	71	70	68	66	65	64	63	61
	60	69	69	69	69	67	66	64	63	62	61	60	59
	70	65	65	65	65	64	63	62	60	59	58	58	57
	80	61	61	61	61	61	60	59	58	57	56	56	54
	90	58	58	58	58	58	58	57	56	55	54	54	53

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft							Panel Orientation: Portrait				
Table 31		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	116	116	114	104	95	89	82	77	75	73	69
	10	102	102	102	101	100	95	89	82	77	75	73	69
	20	86	86	86	86	86	86	86	82	77	75	73	69
	30	74	74	74	74	74	74	74	74	74	73	73	69
	40	65	65	65	65	65	65	65	65	65	65	65	65
	50	59	59	59	59	59	59	59	59	59	59	59	59
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	100	90	86	82	75	69	65	60	57	55	53	50
	10	100	90	86	82	75	69	65	60	57	55	53	50
	20	86	86	86	82	75	69	65	60	57	55	53	50
	30	74	74	74	74	74	69	65	60	57	55	53	50
	40	65	65	65	65	65	65	65	60	57	55	53	50
	50	59	59	59	59	59	59	59	59	57	55	53	50
	60	54	54	54	54	54	54	54	54	54	54	53	50
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 3	0	79	71	68	65	59	55	51	48	45	44	42	40
	10	79	71	68	65	59	55	51	48	45	44	42	40
	20	79	71	68	65	59	55	51	48	45	44	42	40
	30	74	71	68	65	59	55	51	48	45	44	42	40
	40	65	65	65	65	59	55	51	48	45	44	42	40
	50	59	59	59	59	59	55	51	48	45	44	42	40
	60	54	54	54	54	54	54	51	48	45	44	42	40
	70	50	50	50	50	50	50	50	48	45	44	42	40
	80	48	48	48	48	48	48	48	48	45	44	42	40
	90	44	44	44	44	44	44	44	44	44	44	42	40

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

 Mean Roof Height: $30 < h \leq 60$ ft Panel Orientation: Portrait

Table 32 Roof Angle: $0 < \theta \leq 7$ degrees
 Exposure Category: C

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	
Zone 1	0	116	107	101	97	89	82	76	71	66	64	62	59
	10	102	101	100	97	89	82	76	71	66	64	62	59
	20	86	86	86	86	86	82	76	71	66	64	62	59
	30	74	74	74	74	74	74	73	71	66	64	62	59
	40	65	65	65	65	65	65	65	65	65	64	62	59
	50	59	59	59	59	59	59	59	59	59	59	59	58
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	86	77	74	70	65	60	56	52	49	48	46	43
	10	86	77	74	70	65	60	56	52	49	48	46	43
	20	86	77	74	70	65	60	56	52	49	48	46	43
	30	74	74	74	70	65	60	56	52	49	48	46	43
	40	65	65	65	65	65	60	56	52	49	48	46	43
	50	59	59	59	59	59	59	56	52	49	48	46	43
	60	54	54	54	54	54	54	54	52	49	48	46	43
	70	50	50	50	50	50	50	50	50	49	48	46	43
	80	48	48	48	48	48	48	48	48	48	48	46	43
	90	44	44	44	44	44	44	44	44	44	44	44	43
Zone 3	0	68	61	58	56	51	48	44	41	39	38	37	35
	10	68	61	58	56	51	48	44	41	39	38	37	35
	20	68	61	58	56	51	48	44	41	39	38	37	35
	30	68	61	58	56	51	48	44	41	39	38	37	35
	40	65	61	58	56	51	48	44	41	39	38	37	35
	50	59	59	58	56	51	48	44	41	39	38	37	35
	60	54	54	54	54	51	48	44	41	39	38	37	35
	70	50	50	50	50	50	48	44	41	39	38	37	35
	80	48	48	48	48	48	48	44	41	39	38	37	35
	90	44	44	44	44	44	44	44	41	39	38	37	35

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft										Panel Orientation: Portrait	
		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
Zone 1	0	109	98	93	89	82	75	70	65	61	60	58	55
	10	101	98	93	89	82	75	70	65	61	60	58	55
	20	86	86	86	86	82	75	70	65	61	60	58	55
	30	74	74	74	74	74	73	70	65	61	60	58	55
	40	65	65	65	65	65	65	65	65	61	60	58	55
	50	59	59	59	59	59	59	59	59	59	59	58	55
	60	54	54	54	54	54	54	54	54	54	54	54	54
	70	50	50	50	50	50	50	50	50	50	50	50	50
	80	48	48	48	48	48	48	48	48	48	48	48	48
	90	44	44	44	44	44	44	44	44	44	44	44	44
Zone 2	0	79	71	68	65	60	55	51	48	45	44	43	40
	10	79	71	68	65	60	55	51	48	45	44	43	40
	20	79	71	68	65	60	55	51	48	45	44	43	40
	30	74	71	68	65	60	55	51	48	45	44	43	40
	40	65	65	65	65	60	55	51	48	45	44	43	40
	50	59	59	59	59	59	55	51	48	45	44	43	40
	60	54	54	54	54	54	54	51	48	45	44	43	40
	70	50	50	50	50	50	50	50	48	45	44	43	40
	80	48	48	48	48	48	48	48	48	45	44	43	40
	90	44	44	44	44	44	44	44	44	44	44	43	40
Zone 3	0	62	56	54	52	48	44	41	38	36	35	34	32
	10	62	56	54	52	48	44	41	38	36	35	34	32
	20	62	56	54	52	48	44	41	38	36	35	34	32
	30	62	56	54	52	48	44	41	38	36	35	34	32
	40	62	56	54	52	48	44	41	38	36	35	34	32
	50	59	56	54	52	48	44	41	38	36	35	34	32
	60	54	54	54	52	48	44	41	38	36	35	34	32
	70	50	50	50	50	48	44	41	38	36	35	34	32
	80	48	48	48	48	48	44	41	38	36	35	34	32
	90	44	44	44	44	44	44	41	38	36	35	34	32

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft								Panel Orientation: Portrait			
Table 34		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	116	116	114	112	106	98	91	85	80	78	75	71
	10	99	97	96	95	92	90	87	85	80	78	75	71
	20	80	80	80	79	78	76	75	73	72	71	71	69
	30	67	67	67	67	67	67	67	66	64	64	63	62
	40	59	59	59	59	59	59	59	59	59	58	58	57
	50	54	54	54	54	54	54	54	54	54	54	54	53
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	100	90	86	83	76	70	66	61	58	56	54	51
	10	99	90	86	83	76	70	66	61	58	56	54	51
	20	80	80	80	79	76	70	66	61	58	56	54	51
	30	67	67	67	67	67	67	66	61	58	56	54	51
	40	59	59	59	59	59	59	59	59	58	56	54	51
	50	54	54	54	54	54	54	54	54	54	54	54	51
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	80	73	69	66	61	57	53	49	46	45	44	41
	10	80	73	69	66	61	57	53	49	46	45	44	41
	20	80	73	69	66	61	57	53	49	46	45	44	41
	30	67	67	67	66	61	57	53	49	46	45	44	41
	40	59	59	59	59	59	57	53	49	46	45	44	41
	50	54	54	54	54	54	54	53	49	46	45	44	41
	60	49	49	49	49	49	49	49	49	46	45	44	41
	70	46	46	46	46	46	46	46	46	46	45	44	41
	80	43	43	43	43	43	43	43	43	43	43	43	41
	90	41	41	41	41	41	41	41	41	41	41	41	41

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

 Mean Roof Height: $30 < h \leq 60$ ft Panel Orientation: Portrait

Table 35 Roof Angle: $7 < \theta \leq 27$ degrees Exposure Category: C

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	114	109	104	99	91	84	79	74	69	67	65	62
	10	96	93	92	90	88	84	79	74	69	67	65	62
	20	80	78	77	77	75	73	72	70	68	67	65	62
	30	67	67	67	67	67	65	64	63	62	61	60	59
	40	59	59	59	59	59	59	59	58	57	56	56	55
	50	54	54	54	54	54	54	54	54	53	52	52	51
	60	49	49	49	49	49	49	49	49	49	49	49	48
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	86	78	75	71	66	61	57	53	50	48	48	45
	10	86	78	75	71	66	61	57	53	50	48	48	45
	20	80	78	75	71	66	61	57	53	50	48	48	45
	30	67	67	67	67	66	61	57	53	50	48	48	45
	40	59	59	59	59	59	59	57	53	50	48	48	45
	50	54	54	54	54	54	54	54	53	50	48	48	45
	60	49	49	49	49	49	49	49	49	49	48	48	45
	70	46	46	46	46	46	46	46	46	46	46	46	45
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	69	63	60	57	53	49	46	43	40	39	38	36
	10	69	63	60	57	53	49	46	43	40	39	38	36
	20	69	63	60	57	53	49	46	43	40	39	38	36
	30	67	63	60	57	53	49	46	43	40	39	38	36
	40	59	59	59	57	53	49	46	43	40	39	38	36
	50	54	54	54	54	53	49	46	43	40	39	38	36
	60	49	49	49	49	49	49	46	43	40	39	38	36
	70	46	46	46	46	46	46	46	43	40	39	38	36
	80	43	43	43	43	43	43	43	43	40	39	38	36
	90	41	41	41	41	41	41	41	41	40	39	38	36

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft										Panel Orientation: Portrait	
Table 36		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	110	101	96	92	85	78	73	68	64	62	60	57
	10	94	91	89	88	85	78	73	68	64	62	60	57
	20	79	77	76	75	73	71	70	68	64	62	60	57
	30	67	67	67	67	65	64	63	61	60	59	59	57
	40	59	59	59	59	59	59	58	57	55	55	54	53
	50	54	54	54	54	54	54	53	53	52	51	51	50
	60	49	49	49	49	49	49	49	49	49	48	48	48
	70	46	46	46	46	46	46	46	46	46	46	46	45
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	80	72	69	66	61	56	53	49	46	45	44	41
	10	80	72	69	66	61	56	53	49	46	45	44	41
	20	79	72	69	66	61	56	53	49	46	45	44	41
	30	67	67	67	66	61	56	53	49	46	45	44	41
	40	59	59	59	59	59	56	53	49	46	45	44	41
	50	54	54	54	54	54	54	53	49	46	45	44	41
	60	49	49	49	49	49	49	49	49	46	45	44	41
	70	46	46	46	46	46	46	46	46	46	45	44	41
	80	43	43	43	43	43	43	43	43	43	43	43	41
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	64	58	55	53	49	45	42	40	37	36	35	33
	10	64	58	55	53	49	45	42	40	37	36	35	33
	20	64	58	55	53	49	45	42	40	37	36	35	33
	30	64	58	55	53	49	45	42	40	37	36	35	33
	40	59	58	55	53	49	45	42	40	37	36	35	33
	50	54	54	54	53	49	45	42	40	37	36	35	33
	60	49	49	49	49	49	45	42	40	37	36	35	33
	70	46	46	46	46	46	45	42	40	37	36	35	33
	80	43	43	43	43	43	43	42	40	37	36	35	33
	90	41	41	41	41	41	41	41	40	37	36	35	33

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

 Mean Roof Height: $30 < h \leq 60$ ft Panel Orientation: Portrait

Table 37 Roof Angle: $27 < \theta \leq 45$ degrees
 Exposure Category: B

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	106	100	97	94	88	84	79	75	72	70	68	65
	10	94	91	89	87	84	81	78	75	72	70	68	65
	20	82	79	78	77	75	72	70	68	66	65	64	62
	30	73	71	70	70	68	66	64	63	61	60	60	58
	40	65	65	65	64	63	61	60	59	57	57	56	55
	50	59	59	59	59	58	57	56	55	54	53	53	52
	60	55	55	55	55	55	54	53	52	51	51	50	49
	70	51	51	51	51	51	51	51	50	49	48	48	48
	80	48	48	48	48	48	48	48	48	48	46	46	45
	90	45	45	45	45	45	45	45	45	45	45	44	44
Zone 2	0	106	100	97	94	88	83	77	72	68	66	64	61
	10	94	91	89	87	84	81	77	72	68	66	64	61
	20	82	79	78	77	75	72	70	68	66	65	64	61
	30	73	71	70	70	68	66	64	63	61	60	60	58
	40	65	65	65	64	63	61	60	59	57	57	56	55
	50	59	59	59	59	58	57	56	55	54	53	53	52
	60	55	55	55	55	55	54	53	52	51	51	50	49
	70	51	51	51	51	51	51	51	50	49	48	48	48
	80	48	48	48	48	48	48	48	48	48	46	46	45
	90	45	45	45	45	45	45	45	45	45	45	44	44
Zone 3	0	106	100	97	94	88	83	77	72	68	66	64	61
	10	94	91	89	87	84	81	77	72	68	66	64	61
	20	82	79	78	77	75	72	70	68	66	65	64	61
	30	73	71	70	70	68	66	64	63	61	60	60	58
	40	65	65	65	64	63	61	60	59	57	57	56	55
	50	59	59	59	59	58	57	56	55	54	53	53	52
	60	55	55	55	55	55	54	53	52	51	51	50	49
	70	51	51	51	51	51	51	51	50	49	48	48	48
	80	48	48	48	48	48	48	48	48	48	46	46	45
	90	45	45	45	45	45	45	45	45	45	45	44	44

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft										Panel Orientation: Portrait	
		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	96	90	87	84	79	75	71	67	63	62	60	57
	10	89	85	83	81	78	75	71	67	63	62	60	57
	20	78	75	74	73	70	68	65	63	61	60	59	57
	30	70	68	67	66	65	63	61	59	57	56	55	54
	40	65	63	62	62	60	58	57	55	54	53	52	51
	50	59	59	58	58	56	55	54	52	51	50	50	49
	60	55	55	55	54	53	52	51	50	49	48	48	48
	70	51	51	51	51	51	50	49	48	48	46	46	45
	80	48	48	48	48	48	48	48	46	45	44	44	43
	90	45	45	45	45	45	45	45	44	43	43	42	42
Zone 2	0	96	90	87	83	77	72	67	63	59	57	56	53
	10	89	85	83	81	77	72	67	63	59	57	56	53
	20	78	75	74	73	70	68	65	63	59	57	56	53
	30	70	68	67	66	65	63	61	59	57	56	55	53
	40	65	63	62	62	60	58	57	55	54	53	52	51
	50	59	59	58	58	56	55	54	52	51	50	50	49
	60	55	55	55	54	53	52	51	50	49	48	48	48
	70	51	51	51	51	51	50	49	48	48	46	46	45
	80	48	48	48	48	48	48	48	46	45	44	44	43
	90	45	45	45	45	45	45	45	44	43	43	42	42
Zone 3	0	96	90	87	83	77	72	67	63	59	57	56	53
	10	89	85	83	81	77	72	67	63	59	57	56	53
	20	78	75	74	73	70	68	65	63	59	57	56	53
	30	70	68	67	66	65	63	61	59	57	56	55	53
	40	65	63	62	62	60	58	57	55	54	53	52	51
	50	59	59	58	58	56	55	54	52	51	50	50	49
	60	55	55	55	54	53	52	51	50	49	48	48	48
	70	51	51	51	51	51	50	49	48	48	46	46	45
	80	48	48	48	48	48	48	48	46	45	44	44	43
	90	45	45	45	45	45	45	45	44	43	43	42	42

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft										Panel Orientation: Portrait	
		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	91	85	82	80	75	70	66	63	59	58	56	54
	10	86	82	80	78	75	70	66	63	59	58	56	54
	20	76	73	72	70	68	65	63	60	58	57	56	54
	30	69	67	66	65	63	61	59	57	55	54	53	51
	40	63	62	61	60	58	57	55	53	52	51	50	49
	50	59	58	57	56	55	54	52	51	49	49	48	48
	60	55	54	54	53	52	51	50	48	48	48	46	45
	70	51	51	51	51	50	49	48	46	45	45	44	43
	80	48	48	48	48	48	46	46	45	44	43	43	42
	90	45	45	45	45	45	45	44	43	42	42	41	41
Zone 2	0	91	85	81	78	72	66	62	58	55	53	52	49
	10	86	82	80	78	72	66	62	58	55	53	52	49
	20	76	73	72	70	68	65	62	58	55	53	52	49
	30	69	67	66	65	63	61	59	57	55	53	52	49
	40	63	62	61	60	58	57	55	53	52	51	50	49
	50	59	58	57	56	55	54	52	51	49	49	48	48
	60	55	54	54	53	52	51	50	48	48	48	46	45
	70	51	51	51	51	50	49	48	46	45	45	44	43
	80	48	48	48	48	48	46	46	45	44	43	43	42
	90	45	45	45	45	45	45	44	43	42	42	41	41
Zone 3	0	91	85	81	78	72	66	62	58	55	53	52	49
	10	86	82	80	78	72	66	62	58	55	53	52	49
	20	76	73	72	70	68	65	62	58	55	53	52	49
	30	69	67	66	65	63	61	59	57	55	53	52	49
	40	63	62	61	60	58	57	55	53	52	51	50	49
	50	59	58	57	56	55	54	52	51	49	49	48	48
	60	55	54	54	53	52	51	50	48	48	48	46	45
	70	51	51	51	51	50	49	48	46	45	45	44	43
	80	48	48	48	48	48	46	46	45	44	43	43	42
	90	45	45	45	45	45	45	44	43	42	42	41	41

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 67.5"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft								Panel Orientation: Landscape			
Table 40		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	121	121	112	105	98	95	92	87
	10	120	120	119	119	117	116	112	105	98	95	92	87
	20	101	101	101	101	101	101	101	101	98	95	92	87
	30	90	90	90	90	90	90	90	90	90	90	90	87
	40	82	82	82	82	82	82	82	82	82	82	82	82
	50	74	74	74	74	74	74	74	74	74	74	74	74
	60	68	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	121	114	109	104	95	88	82	77	72	70	68	64
	10	120	114	109	104	95	88	82	77	72	70	68	64
	20	101	101	101	101	95	88	82	77	72	70	68	64
	30	90	90	90	90	90	88	82	77	72	70	68	64
	40	82	82	82	82	82	82	82	77	72	70	68	64
	50	74	74	74	74	74	74	74	74	72	70	68	64
	60	68	68	68	68	68	68	68	68	68	68	68	64
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 3	0	100	90	86	82	76	70	65	61	57	55	54	51
	10	100	90	86	82	76	70	65	61	57	55	54	51
	20	100	90	86	82	76	70	65	61	57	55	54	51
	30	90	90	86	82	76	70	65	61	57	55	54	51
	40	82	82	82	82	76	70	65	61	57	55	54	51
	50	74	74	74	74	74	70	65	61	57	55	54	51
	60	68	68	68	68	68	68	65	61	57	55	54	51
	70	64	64	64	64	64	64	64	61	57	55	54	51
	80	60	60	60	60	60	60	60	60	57	55	54	51
	90	56	56	56	56	56	56	56	56	56	55	54	51

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft							Panel Orientation: Landscape				
Table 41		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	112	104	96	90	84	82	79	75
	10	119	118	117	116	112	104	96	90	84	82	79	75
	20	101	101	101	101	101	100	96	90	84	82	79	75
	30	90	90	90	90	90	90	90	90	84	82	79	75
	40	82	82	82	82	82	82	82	82	82	82	79	75
	50	74	74	74	74	74	74	74	74	74	74	74	74
	60	68	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	109	98	93	89	82	76	71	66	62	60	58	55
	10	109	98	93	89	82	76	71	66	62	60	58	55
	20	101	98	93	89	82	76	71	66	62	60	58	55
	30	90	90	90	89	82	76	71	66	62	60	58	55
	40	82	82	82	82	82	76	71	66	62	60	58	55
	50	74	74	74	74	74	74	71	66	62	60	58	55
	60	68	68	68	68	68	68	68	66	62	60	58	55
	70	64	64	64	64	64	64	64	64	62	60	58	55
	80	60	60	60	60	60	60	60	60	60	60	58	55
	90	56	56	56	56	56	56	56	56	56	56	56	55
Zone 3	0	86	78	74	71	65	60	56	53	49	48	48	44
	10	86	78	74	71	65	60	56	53	49	48	48	44
	20	86	78	74	71	65	60	56	53	49	48	48	44
	30	86	78	74	71	65	60	56	53	49	48	48	44
	40	82	78	74	71	65	60	56	53	49	48	48	44
	50	74	74	74	71	65	60	56	53	49	48	48	44
	60	68	68	68	68	65	60	56	53	49	48	48	44
	70	64	64	64	64	64	60	56	53	49	48	48	44
	80	60	60	60	60	60	60	56	53	49	48	48	44
	90	56	56	56	56	56	56	56	53	49	48	48	44

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft								Panel Orientation: Landscape			
Table 42		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	119	113	104	96	89	83	78	76	73	69
	10	118	117	116	113	104	96	89	83	78	76	73	69
	20	101	101	101	101	100	96	89	83	78	76	73	69
	30	90	90	90	90	90	90	89	83	78	76	73	69
	40	82	82	82	82	82	82	82	82	78	76	73	69
	50	74	74	74	74	74	74	74	74	74	74	73	69
	60	68	68	68	68	68	68	68	68	68	68	68	68
	70	64	64	64	64	64	64	64	64	64	64	64	64
	80	60	60	60	60	60	60	60	60	60	60	60	60
	90	56	56	56	56	56	56	56	56	56	56	56	56
Zone 2	0	100	91	86	83	76	70	65	61	57	56	54	51
	10	100	91	86	83	76	70	65	61	57	56	54	51
	20	100	91	86	83	76	70	65	61	57	56	54	51
	30	90	90	86	83	76	70	65	61	57	56	54	51
	40	82	82	82	82	76	70	65	61	57	56	54	51
	50	74	74	74	74	74	70	65	61	57	56	54	51
	60	68	68	68	68	68	68	65	61	57	56	54	51
	70	64	64	64	64	64	64	64	61	57	56	54	51
	80	60	60	60	60	60	60	60	60	57	56	54	51
	90	56	56	56	56	56	56	56	56	56	56	54	51
Zone 3	0	79	72	69	66	60	56	52	49	46	44	43	41
	10	79	72	69	66	60	56	52	49	46	44	43	41
	20	79	72	69	66	60	56	52	49	46	44	43	41
	30	79	72	69	66	60	56	52	49	46	44	43	41
	40	79	72	69	66	60	56	52	49	46	44	43	41
	50	74	72	69	66	60	56	52	49	46	44	43	41
	60	68	68	68	66	60	56	52	49	46	44	43	41
	70	64	64	64	64	60	56	52	49	46	44	43	41
	80	60	60	60	60	60	56	52	49	46	44	43	41
	90	56	56	56	56	56	56	52	49	46	44	43	41

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft								Panel Orientation: Landscape			
Table 43		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	121	121	116	108	102	99	96	91
	10	119	117	116	115	113	111	109	107	102	99	96	91
	20	101	101	101	101	99	97	95	93	91	90	90	88
	30	86	86	86	86	86	86	85	83	82	81	81	79
	40	75	75	75	75	75	75	75	75	75	74	74	73
	50	68	68	68	68	68	68	68	68	68	68	68	68
	60	63	63	63	63	63	63	63	63	63	63	63	63
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 2	0	121	115	110	105	97	89	83	78	73	71	69	65
	10	119	115	110	105	97	89	83	78	73	71	69	65
	20	101	101	101	101	97	89	83	78	73	71	69	65
	30	86	86	86	86	86	86	83	78	73	71	69	65
	40	75	75	75	75	75	75	75	75	73	71	69	65
	50	68	68	68	68	68	68	68	68	68	68	68	65
	60	63	63	63	63	63	63	63	63	63	63	63	63
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 3	0	102	92	88	84	78	72	67	63	59	57	56	53
	10	102	92	88	84	78	72	67	63	59	57	56	53
	20	101	92	88	84	78	72	67	63	59	57	56	53
	30	86	86	86	84	78	72	67	63	59	57	56	53
	40	75	75	75	75	75	72	67	63	59	57	56	53
	50	68	68	68	68	68	68	67	63	59	57	56	53
	60	63	63	63	63	63	63	63	63	59	57	56	53
	70	58	58	58	58	58	58	58	58	58	57	56	53
	80	55	55	55	55	55	55	55	55	55	55	55	53
	90	52	52	52	52	52	52	52	52	52	52	52	52

Notes:

1. Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
2. Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft										Panel Orientation: Landscape	
Table 44		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	121	121	116	107	100	93	88	85	83	78
	10	116	114	113	112	109	107	100	93	88	85	83	78
	20	101	99	98	97	95	93	91	89	87	85	83	78
	30	86	86	86	86	85	83	81	80	78	78	77	75
	40	75	75	75	75	75	75	75	73	72	71	71	70
	50	68	68	68	68	68	68	68	68	67	67	66	65
	60	63	63	63	63	63	63	63	63	63	63	62	61
	70	58	58	58	58	58	58	58	58	58	58	58	58
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 2	0	109	99	95	91	83	77	72	67	63	62	60	57
	10	109	99	95	91	83	77	72	67	63	62	60	57
	20	101	99	95	91	83	77	72	67	63	62	60	57
	30	86	86	86	86	83	77	72	67	63	62	60	57
	40	75	75	75	75	75	75	72	67	63	62	60	57
	50	68	68	68	68	68	68	68	67	63	62	60	57
	60	63	63	63	63	63	63	63	63	63	62	60	57
	70	58	58	58	58	58	58	58	58	58	58	58	57
	80	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52
Zone 3	0	88	80	76	73	67	62	58	54	51	50	48	46
	10	88	80	76	73	67	62	58	54	51	50	48	46
	20	88	80	76	73	67	62	58	54	51	50	48	46
	30	86	80	76	73	67	62	58	54	51	50	48	46
	40	75	75	75	73	67	62	58	54	51	50	48	46
	50	68	68	68	68	67	62	58	54	51	50	48	46
	60	63	63	63	63	63	62	58	54	51	50	48	46
	70	58	58	58	58	58	58	58	54	51	50	48	46
	80	55	55	55	55	55	55	55	54	51	50	48	46
	90	52	52	52	52	52	52	52	52	51	50	48	46

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft										Panel Orientation: Landscape		
		Roof Angle: $7 < \theta \leq 27$ degrees												
		Exposure Category: D												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	121	121	121	117	107	99	92	87	81	79	77	77	73
	10	114	112	111	109	107	99	92	87	81	79	77	77	73
	20	100	98	97	95	93	91	88	86	81	79	77	77	73
	30	86	86	85	85	83	81	80	78	76	75	75	75	73
	40	75	75	75	75	75	74	73	72	70	70	69	68	
	50	68	68	68	68	68	68	68	67	66	65	65	64	
	60	63	63	63	63	63	63	63	63	62	61	61	60	
	70	58	58	58	58	58	58	58	58	58	58	58	58	57
	80	55	55	55	55	55	55	55	55	55	55	55	55	55
	90	52	52	52	52	52	52	52	52	52	52	52	52	52
Zone 2	0	101	92	88	84	77	72	67	62	59	57	55	55	52
	10	101	92	88	84	77	72	67	62	59	57	55	55	52
	20	100	92	88	84	77	72	67	62	59	57	55	55	52
	30	86	86	85	84	77	72	67	62	59	57	55	55	52
	40	75	75	75	75	75	72	67	62	59	57	55	55	52
	50	68	68	68	68	68	68	67	62	59	57	55	55	52
	60	63	63	63	63	63	63	63	62	59	57	55	55	52
	70	58	58	58	58	58	58	58	58	58	57	55	55	52
	80	55	55	55	55	55	55	55	55	55	55	55	55	52
	90	52	52	52	52	52	52	52	52	52	52	52	52	52
Zone 3	0	81	74	70	67	62	58	54	50	48	46	45	42	
	10	81	74	70	67	62	58	54	50	48	46	45	42	
	20	81	74	70	67	62	58	54	50	48	46	45	42	
	30	81	74	70	67	62	58	54	50	48	46	45	42	
	40	75	74	70	67	62	58	54	50	48	46	45	42	
	50	68	68	68	67	62	58	54	50	48	46	45	42	
	60	63	63	63	63	62	58	54	50	48	46	45	42	
	70	58	58	58	58	58	58	54	50	48	46	45	42	
	80	55	55	55	55	55	55	54	50	48	46	45	42	
	90	52	52	52	52	52	52	52	50	48	46	45	42	

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft							Panel Orientation: Landscape				
Table 46		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	121	121	119	116	112	106	101	96	91	89	87	83
	10	119	115	113	111	107	103	99	95	91	89	87	83
	20	104	101	99	98	95	92	89	86	84	82	81	79
	30	93	91	89	88	86	84	82	80	78	77	76	74
	40	83	83	82	81	80	78	76	74	73	72	71	69
	50	75	75	75	75	74	73	71	70	69	68	67	66
	60	69	69	69	69	69	69	68	66	65	64	64	63
	70	65	65	65	65	65	65	64	63	62	62	61	60
	80	61	61	61	61	61	61	61	60	59	59	58	58
	90	58	58	58	58	58	58	58	58	57	57	56	55
Zone 2	0	121	121	119	116	112	105	98	92	86	84	82	77
	10	119	115	113	111	107	103	98	92	86	84	82	77
	20	104	101	99	98	95	92	89	86	84	82	81	77
	30	93	91	89	88	86	84	82	80	78	77	76	74
	40	83	83	82	81	80	78	76	74	73	72	71	69
	50	75	75	75	75	74	73	71	70	69	68	67	66
	60	69	69	69	69	69	69	68	66	65	64	64	63
	70	65	65	65	65	65	65	64	63	62	62	61	60
	80	61	61	61	61	61	61	61	60	59	59	58	58
	90	58	58	58	58	58	58	58	58	57	57	56	55
Zone 3	0	121	121	119	116	112	105	98	92	86	84	82	77
	10	119	115	113	111	107	103	98	92	86	84	82	77
	20	104	101	99	98	95	92	89	86	84	82	81	77
	30	93	91	89	88	86	84	82	80	78	77	76	74
	40	83	83	82	81	80	78	76	74	73	72	71	69
	50	75	75	75	75	74	73	71	70	69	68	67	66
	60	69	69	69	69	69	69	68	66	65	64	64	63
	70	65	65	65	65	65	65	64	63	62	62	61	60
	80	61	61	61	61	61	61	61	60	59	59	58	58
	90	58	58	58	58	58	58	58	58	57	57	56	55

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft							Panel Orientation: Landscape				
Table 48		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	119	113	111	107	101	95	90	85	81	79	77	73
	10	113	108	106	103	99	95	90	85	81	79	77	73
	20	99	96	94	92	89	86	83	80	77	76	75	72
	30	89	87	86	84	82	79	77	75	72	71	70	68
	40	82	80	79	78	76	74	72	70	68	67	66	65
	50	75	75	74	73	71	70	68	66	65	64	63	62
	60	69	69	69	69	68	66	65	63	62	61	60	59
	70	65	65	65	65	64	63	62	61	59	59	58	57
	80	61	61	61	61	61	60	59	58	57	56	56	55
	90	58	58	58	58	58	58	57	56	55	54	54	53
Zone 2	0	119	113	111	106	98	91	85	80	75	73	71	67
	10	113	108	106	103	98	91	85	80	75	73	71	67
	20	99	96	94	92	89	86	83	80	75	73	71	67
	30	89	87	86	84	82	79	77	75	72	71	70	67
	40	82	80	79	78	76	74	72	70	68	67	66	65
	50	75	75	74	73	71	70	68	66	65	64	63	62
	60	69	69	69	69	68	66	65	63	62	61	60	59
	70	65	65	65	65	64	63	62	61	59	59	58	57
	80	61	61	61	61	61	60	59	58	57	56	56	55
	90	58	58	58	58	58	58	57	56	55	54	54	53
Zone 3	0	119	113	111	106	98	91	85	80	75	73	71	67
	10	113	108	106	103	98	91	85	80	75	73	71	67
	20	99	96	94	92	89	86	83	80	75	73	71	67
	30	89	87	86	84	82	79	77	75	72	71	70	67
	40	82	80	79	78	76	74	72	70	68	67	66	65
	50	75	75	74	73	71	70	68	66	65	64	63	62
	60	69	69	69	69	68	66	65	63	62	61	60	59
	70	65	65	65	65	64	63	62	61	59	59	58	57
	80	61	61	61	61	61	60	59	58	57	56	56	55
	90	58	58	58	58	58	58	57	56	55	54	54	53

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $30 < h \leq 60$ ft							Panel Orientation: Landscape				
Table 48		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	114	108	105	101	95	89	84	80	75	74	72	68
	10	109	104	102	99	95	89	84	80	75	74	72	68
	20	97	93	91	89	86	83	80	77	74	72	71	68
	30	88	85	83	82	79	77	74	72	70	68	67	65
	40	81	78	77	76	74	72	70	68	66	65	64	62
	50	75	73	72	72	70	68	66	64	63	62	61	59
	60	69	69	68	68	66	65	63	62	60	59	59	57
	70	65	65	65	64	63	62	60	59	58	57	56	55
	80	61	61	61	61	60	59	58	57	56	55	54	53
	90	58	58	58	58	58	57	56	55	54	53	53	51
Zone 2	0	114	107	103	98	91	84	79	74	69	68	66	62
	10	109	104	102	98	91	84	79	74	69	68	66	62
	20	97	93	91	89	86	83	79	74	69	68	66	62
	30	88	85	83	82	79	77	74	72	69	68	66	62
	40	81	78	77	76	74	72	70	68	66	65	64	62
	50	75	73	72	72	70	68	66	64	63	62	61	59
	60	69	69	68	68	66	65	63	62	60	59	59	57
	70	65	65	65	64	63	62	60	59	58	57	56	55
	80	61	61	61	61	60	59	58	57	56	55	54	53
	90	58	58	58	58	58	57	56	55	54	53	53	51
Zone 3	0	114	107	103	98	91	84	79	74	69	68	66	62
	10	109	104	102	98	91	84	79	74	69	68	66	62
	20	97	93	91	89	86	83	79	74	69	68	66	62
	30	88	85	83	82	79	77	74	72	69	68	66	62
	40	81	78	77	76	74	72	70	68	66	65	64	62
	50	75	73	72	72	70	68	66	64	63	62	61	59
	60	69	69	68	68	66	65	63	62	60	59	59	57
	70	65	65	65	64	63	62	60	59	58	57	56	55
	80	61	61	61	61	60	59	58	57	56	55	54	53
	90	58	58	58	58	58	57	56	55	54	53	53	51

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in landscape orientation with a maximum width of 42"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft							Panel Orientation: Portrait				
Table 49		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	114	114	108	103	94	87	80	75	70	68	66	62
	10	96	96	95	95	94	87	80	75	70	68	66	62
	20	79	79	79	79	79	79	78	75	70	68	66	62
	30	67	67	67	67	67	67	67	67	67	66	66	62
	40	59	59	59	59	59	59	59	59	59	59	59	59
	50	53	53	53	53	53	53	53	53	53	53	53	53
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	45	45	45	45	45	45	45	45	45	45	45	45
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	40	40	40	40	40	40	40	40	40	40	40	40
Zone 2	0	91	82	78	74	68	63	59	55	51	50	48	46
	10	91	82	78	74	68	63	59	55	51	50	48	46
	20	79	79	78	74	68	63	59	55	51	50	48	46
	30	67	67	67	67	67	63	59	55	51	50	48	46
	40	59	59	59	59	59	59	59	55	51	50	48	46
	50	53	53	53	53	53	53	53	53	51	50	48	46
	60	49	49	49	49	49	49	49	49	49	49	48	46
	70	45	45	45	45	45	45	45	45	45	45	45	45
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	40	40	40	40	40	40	40	40	40	40	40	40
Zone 3	0	71	64	61	59	54	50	46	43	41	40	38	36
	10	71	64	61	59	54	50	46	43	41	40	38	36
	20	71	64	61	59	54	50	46	43	41	40	38	36
	30	67	64	61	59	54	50	46	43	41	40	38	36
	40	59	59	59	59	54	50	46	43	41	40	38	36
	50	53	53	53	53	53	50	46	43	41	40	38	36
	60	49	49	49	49	49	49	46	43	41	40	38	36
	70	45	45	45	45	45	45	45	43	41	40	38	36
	80	43	43	43	43	43	43	43	43	41	40	38	36
	90	40	40	40	40	40	40	40	40	40	40	38	36

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft							Panel Orientation: Portrait				
Table 50		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	108	97	92	88	80	74	69	64	60	58	57	54
	10	95	94	92	88	80	74	69	64	60	58	57	54
	20	79	79	79	79	78	74	69	64	60	58	57	54
	30	67	67	67	67	67	67	66	64	60	58	57	54
	40	59	59	59	59	59	59	59	59	59	58	57	54
	50	53	53	53	53	53	53	53	53	53	53	53	53
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	45	45	45	45	45	45	45	45	45	45	45	45
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	40	40	40	40	40	40	40	40	40	40	40	40
Zone 2	0	78	70	67	64	59	54	50	48	44	43	42	39
	10	78	70	67	64	59	54	50	48	44	43	42	39
	20	78	70	67	64	59	54	50	48	44	43	42	39
	30	67	67	67	64	59	54	50	48	44	43	42	39
	40	59	59	59	59	59	54	50	48	44	43	42	39
	50	53	53	53	53	53	53	50	48	44	43	42	39
	60	49	49	49	49	49	49	49	48	44	43	42	39
	70	45	45	45	45	45	45	45	45	44	43	42	39
	80	43	43	43	43	43	43	43	43	43	43	42	39
	90	40	40	40	40	40	40	40	40	40	40	40	39
Zone 3	0	61	55	53	51	46	43	40	37	35	34	33	31
	10	61	55	53	51	46	43	40	37	35	34	33	31
	20	61	55	53	51	46	43	40	37	35	34	33	31
	30	61	55	53	51	46	43	40	37	35	34	33	31
	40	59	55	53	51	46	43	40	37	35	34	33	31
	50	53	53	53	51	46	43	40	37	35	34	33	31
	60	49	49	49	49	46	43	40	37	35	34	33	31
	70	45	45	45	45	45	43	40	37	35	34	33	31
	80	43	43	43	43	43	43	40	37	35	34	33	31
	90	40	40	40	40	40	40	40	37	35	34	33	31

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft							Panel Orientation: Portrait				
Table 51		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	99	89	85	81	74	68	64	59	56	54	52	50
	10	95	89	85	81	74	68	64	59	56	54	52	50
	20	79	79	79	78	74	68	64	59	56	54	52	50
	30	67	67	67	67	67	66	64	59	56	54	52	50
	40	59	59	59	59	59	59	59	59	56	54	52	50
	50	53	53	53	53	53	53	53	53	53	53	52	50
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	45	45	45	45	45	45	45	45	45	45	45	45
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	40	40	40	40	40	40	40	40	40	40	40	40
Zone 2	0	72	65	62	59	54	50	48	44	41	40	39	37
	10	72	65	62	59	54	50	48	44	41	40	39	37
	20	72	65	62	59	54	50	48	44	41	40	39	37
	30	67	65	62	59	54	50	48	44	41	40	39	37
	40	59	59	59	59	54	50	48	44	41	40	39	37
	50	53	53	53	53	53	50	48	44	41	40	39	37
	60	49	49	49	49	49	49	48	44	41	40	39	37
	70	45	45	45	45	45	45	45	44	41	40	39	37
	80	43	43	43	43	43	43	43	43	41	40	39	37
	90	40	40	40	40	40	40	40	40	40	40	39	37
Zone 3	0	57	51	49	48	43	40	37	35	33	32	31	29
	10	57	51	49	48	43	40	37	35	33	32	31	29
	20	57	51	49	48	43	40	37	35	33	32	31	29
	30	57	51	49	48	43	40	37	35	33	32	31	29
	40	57	51	49	48	43	40	37	35	33	32	31	29
	50	53	51	49	48	43	40	37	35	33	32	31	29
	60	49	49	49	48	43	40	37	35	33	32	31	29
	70	45	45	45	45	43	40	37	35	33	32	31	29
	80	43	43	43	43	43	40	37	35	33	32	31	29
	90	40	40	40	40	40	40	37	35	33	32	31	29

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft							Panel Orientation: Portrait				
Table 52		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	112	108	106	104	96	89	83	77	73	70	68	65
	10	90	88	87	86	84	81	79	77	73	70	68	65
	20	72	72	72	72	71	69	68	67	65	65	64	63
	30	61	61	61	61	61	61	60	59	58	58	57	57
	40	54	54	54	54	54	54	54	54	53	53	53	52
	50	49	49	49	49	49	49	49	49	49	49	49	48
	60	45	45	45	45	45	45	45	45	45	45	45	45
	70	42	42	42	42	42	42	42	42	42	42	42	42
	80	39	39	39	39	39	39	39	39	39	39	39	39
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 2	0	91	82	78	75	69	64	59	56	52	51	49	48
	10	90	82	78	75	69	64	59	56	52	51	49	48
	20	72	72	72	72	69	64	59	56	52	51	49	48
	30	61	61	61	61	61	61	59	56	52	51	49	48
	40	54	54	54	54	54	54	54	54	52	51	49	48
	50	49	49	49	49	49	49	49	49	49	49	49	48
	60	45	45	45	45	45	45	45	45	45	45	45	45
	70	42	42	42	42	42	42	42	42	42	42	42	42
	80	39	39	39	39	39	39	39	39	39	39	39	39
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 3	0	73	66	63	60	55	51	48	45	42	41	40	38
	10	73	66	63	60	55	51	48	45	42	41	40	38
	20	72	66	63	60	55	51	48	45	42	41	40	38
	30	61	61	61	60	55	51	48	45	42	41	40	38
	40	54	54	54	54	54	51	48	45	42	41	40	38
	50	49	49	49	49	49	49	48	45	42	41	40	38
	60	45	45	45	45	45	45	45	45	42	41	40	38
	70	42	42	42	42	42	42	42	42	42	41	40	38
	80	39	39	39	39	39	39	39	39	39	39	39	38
	90	37	37	37	37	37	37	37	37	37	37	37	37

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft										Panel Orientation: Portrait		
		Roof Angle: $7 < \theta \leq 27$ degrees												
		Exposure Category: C												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	106	99	94	90	83	77	71	67	63	61	59	56	
	10	87	84	83	82	79	77	71	67	63	61	59	56	
	20	72	71	70	70	68	66	65	63	62	61	59	56	
	30	61	61	61	61	60	59	58	57	56	55	55	54	
	40	54	54	54	54	54	54	53	52	51	51	51	50	
	50	49	49	49	49	49	49	49	49	48	48	48	46	
	60	45	45	45	45	45	45	45	45	45	45	44	44	
	70	42	42	42	42	42	42	42	42	42	42	42	42	
	80	39	39	39	39	39	39	39	39	39	39	39	39	
	90	37	37	37	37	37	37	37	37	37	37	37	37	
Zone 2	0	78	71	68	65	60	55	51	48	45	44	43	40	
	10	78	71	68	65	60	55	51	48	45	44	43	40	
	20	72	71	68	65	60	55	51	48	45	44	43	40	
	30	61	61	61	61	60	55	51	48	45	44	43	40	
	40	54	54	54	54	54	54	51	48	45	44	43	40	
	50	49	49	49	49	49	49	49	48	45	44	43	40	
	60	45	45	45	45	45	45	45	45	45	44	43	40	
	70	42	42	42	42	42	42	42	42	42	42	42	40	
	80	39	39	39	39	39	39	39	39	39	39	39	39	
	90	37	37	37	37	37	37	37	37	37	37	37	37	
Zone 3	0	63	57	54	52	48	44	41	39	36	35	34	32	
	10	63	57	54	52	48	44	41	39	36	35	34	32	
	20	63	57	54	52	48	44	41	39	36	35	34	32	
	30	61	57	54	52	48	44	41	39	36	35	34	32	
	40	54	54	54	52	48	44	41	39	36	35	34	32	
	50	49	49	49	49	48	44	41	39	36	35	34	32	
	60	45	45	45	45	45	44	41	39	36	35	34	32	
	70	42	42	42	42	42	42	41	39	36	35	34	32	
	80	39	39	39	39	39	39	39	39	36	35	34	32	
	90	37	37	37	37	37	37	37	37	36	35	34	32	

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft							Panel Orientation: Portrait				
Table 54		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: D											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	101	91	87	83	77	71	66	62	58	56	55	52
	10	85	82	81	80	77	71	66	62	58	56	55	52
	20	71	70	69	68	66	65	63	61	58	56	55	52
	30	61	61	61	60	59	58	57	56	54	54	53	52
	40	54	54	54	54	54	53	52	51	50	50	49	48
	50	49	49	49	49	49	49	48	48	48	48	46	45
	60	45	45	45	45	45	45	45	45	44	44	44	43
	70	42	42	42	42	42	42	42	42	42	42	41	41
	80	39	39	39	39	39	39	39	39	39	39	39	39
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 2	0	72	66	63	60	55	51	48	45	42	41	40	37
	10	72	66	63	60	55	51	48	45	42	41	40	37
	20	71	66	63	60	55	51	48	45	42	41	40	37
	30	61	61	61	60	55	51	48	45	42	41	40	37
	40	54	54	54	54	54	51	48	45	42	41	40	37
	50	49	49	49	49	49	49	48	45	42	41	40	37
	60	45	45	45	45	45	45	45	45	42	41	40	37
	70	42	42	42	42	42	42	42	42	42	41	40	37
	80	39	39	39	39	39	39	39	39	39	39	39	37
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 3	0	58	53	50	48	44	41	38	36	34	33	32	30
	10	58	53	50	48	44	41	38	36	34	33	32	30
	20	58	53	50	48	44	41	38	36	34	33	32	30
	30	58	53	50	48	44	41	38	36	34	33	32	30
	40	54	53	50	48	44	41	38	36	34	33	32	30
	50	49	49	49	48	44	41	38	36	34	33	32	30
	60	45	45	45	45	44	41	38	36	34	33	32	30
	70	42	42	42	42	42	41	38	36	34	33	32	30
	80	39	39	39	39	39	39	38	36	34	33	32	30
	90	37	37	37	37	37	37	37	36	34	33	32	30

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft										Panel Orientation: Portrait		
		Roof Angle: $27 < \theta \leq 45$ degrees												
		Exposure Category: B												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	97	91	88	86	81	76	72	69	65	63	62	59	
	10	87	84	81	81	78	75	72	69	65	63	62	59	
	20	76	74	71	71	69	67	65	63	61	59	59	57	
	30	68	66	65	65	63	61	60	58	57	55	55	53	
	40	62	61	60	60	58	57	56	54	53	52	52	50	
	50	56	56	56	56	54	53	52	51	50	49	49	48	
	60	51	51	51	51	51	50	49	49	48	48	48	46	
	70	48	48	48	48	48	48	48	46	45	45	45	44	
	80	45	45	45	45	45	45	45	44	44	43	43	42	
	90	43	43	43	43	43	43	43	43	42	41	41	41	
Zone 2	0	97	91	88	86	81	76	71	67	63	60	59	56	
	10	87	84	81	81	78	75	71	67	63	60	59	56	
	20	76	74	71	71	69	67	65	63	61	59	59	56	
	30	68	66	65	65	63	61	60	58	57	55	55	53	
	40	62	61	60	60	58	57	56	54	53	52	52	50	
	50	56	56	56	56	54	53	52	51	50	49	49	48	
	60	51	51	51	51	51	50	49	49	48	48	48	46	
	70	48	48	48	48	48	48	48	46	45	45	45	44	
	80	45	45	45	45	45	45	45	44	44	43	43	42	
	90	43	43	43	43	43	43	43	43	42	41	41	41	
Zone 3	0	97	91	88	86	81	76	71	67	63	60	59	56	
	10	87	84	81	81	78	75	71	67	63	60	59	56	
	20	76	74	71	71	69	67	65	63	61	59	59	56	
	30	68	66	65	65	63	61	60	58	57	55	55	53	
	40	62	61	60	60	58	57	56	54	53	52	52	50	
	50	56	56	56	56	54	53	52	51	50	49	49	48	
	60	51	51	51	51	51	50	49	49	48	48	48	46	
	70	48	48	48	48	48	48	48	46	45	45	45	44	
	80	45	45	45	45	45	45	45	44	44	43	43	42	
	90	43	43	43	43	43	43	43	43	42	41	41	41	

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 60$ ft							Panel Orientation: Portrait				
Table 56		Roof Angle: $27 < \theta \leq 45$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	88	82	79	77	72	68	64	61	58	56	55	52
	10	82	79	75	75	72	68	64	61	58	56	55	52
	20	73	70	67	67	65	63	60	58	56	54	54	52
	30	66	64	62	62	60	58	56	54	53	51	51	49
	40	60	59	57	57	56	54	53	51	50	48	48	48
	50	56	55	54	54	52	51	50	49	48	46	46	45
	60	51	51	51	51	49	48	48	46	45	44	44	43
	70	48	48	48	48	48	46	45	44	43	42	42	41
	80	45	45	45	45	45	44	43	42	42	41	41	40
	90	43	43	43	43	43	42	42	41	40	39	39	39
Zone 2	0	88	82	79	77	71	66	61	58	54	52	51	48
	10	82	79	75	75	71	66	61	58	54	52	51	48
	20	73	70	67	67	65	63	60	58	54	52	51	48
	30	66	64	62	62	60	58	56	54	53	51	51	48
	40	60	59	57	57	56	54	53	51	50	48	48	48
	50	56	55	54	54	52	51	50	49	48	46	46	45
	60	51	51	51	51	49	48	48	46	45	44	44	43
	70	48	48	48	48	48	46	45	44	43	42	42	41
	80	45	45	45	45	45	44	43	42	42	41	41	40
	90	43	43	43	43	43	42	42	41	40	39	39	39
Zone 3	0	88	82	79	77	71	66	61	58	54	52	51	48
	10	82	79	75	75	71	66	61	58	54	52	51	48
	20	73	70	67	67	65	63	60	58	54	52	51	48
	30	66	64	62	62	60	58	56	54	53	51	51	48
	40	60	59	57	57	56	54	53	51	50	48	48	48
	50	56	55	54	54	52	51	50	49	48	46	46	45
	60	51	51	51	51	49	48	48	46	45	44	44	43
	70	48	48	48	48	48	46	45	44	43	42	42	41
	80	45	45	45	45	45	44	43	42	42	41	41	40
	90	43	43	43	43	43	42	42	41	40	39	39	39

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

 Mean Roof Height: $0 < h \leq 60$ ft Panel Orientation: Portrait

Table 57 Roof Angle: $27 < \theta \leq 45$ degrees
 Exposure Category: D

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	84	78	75	73	68	64	60	57	54	53	51	49
	10	79	76	73	72	68	64	60	57	54	53	51	49
	20	71	68	65	65	63	60	58	56	53	52	51	49
	30	64	62	60	60	58	56	54	52	50	49	49	48
	40	59	57	56	56	54	53	51	49	48	46	46	45
	50	55	54	52	52	51	50	48	48	46	44	44	43
	60	51	51	50	50	48	48	46	45	44	43	43	42
	70	48	48	48	48	46	45	44	43	42	41	41	40
	80	45	45	45	45	44	43	42	41	41	40	40	39
	90	43	43	43	43	42	42	41	40	39	38	38	38
Zone 2	0	84	78	73	72	66	61	57	53	50	48	48	45
	10	79	76	73	72	66	61	57	53	50	48	48	45
	20	71	68	65	65	63	60	57	53	50	48	48	45
	30	64	62	60	60	58	56	54	52	50	48	48	45
	40	59	57	56	56	54	53	51	49	48	46	46	45
	50	55	54	52	52	51	50	48	48	46	44	44	43
	60	51	51	50	50	48	48	46	45	44	43	43	42
	70	48	48	48	48	46	45	44	43	42	41	41	40
	80	45	45	45	45	44	43	42	41	41	40	40	39
	90	43	43	43	43	42	42	41	40	39	38	38	38
Zone 3	0	84	78	73	72	66	61	57	53	50	48	48	45
	10	79	76	73	72	66	61	57	53	50	48	48	45
	20	71	68	65	65	63	60	57	53	50	48	48	45
	30	64	62	60	60	58	56	54	52	50	48	48	45
	40	59	57	56	56	54	53	51	49	48	46	46	45
	50	55	54	52	52	51	50	48	48	46	44	44	43
	60	51	51	50	50	48	48	46	45	44	43	43	42
	70	48	48	48	48	46	45	44	43	42	41	41	40
	80	45	45	45	45	44	43	42	41	41	40	40	39
	90	43	43	43	43	42	42	41	40	39	38	38	38

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 82"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Portrait				
Table 58		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	98	98	98	98	98	98	90	84	79	76	74	70
	10	97	97	97	97	96	95	90	84	79	76	74	70
	20	80	80	80	80	80	80	80	79	78	76	74	70
	30	68	68	68	68	68	68	68	68	68	68	68	67
	40	59	59	59	59	59	59	59	59	59	59	59	59
	50	54	54	54	54	54	54	54	54	54	54	54	54
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	98	92	88	84	77	71	66	61	58	56	54	51
	10	97	92	88	84	77	71	66	61	58	56	54	51
	20	80	80	80	80	77	71	66	61	58	56	54	51
	30	68	68	68	68	68	68	66	61	58	56	54	51
	40	59	59	59	59	59	59	59	59	58	56	54	51
	50	54	54	54	54	54	54	54	54	54	54	54	51
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	80	72	69	66	60	56	52	49	46	44	43	41
	10	80	72	69	66	60	56	52	49	46	44	43	41
	20	80	72	69	66	60	56	52	49	46	44	43	41
	30	68	68	68	66	60	56	52	49	46	44	43	41
	40	59	59	59	59	59	56	52	49	46	44	43	41
	50	54	54	54	54	54	54	52	49	46	44	43	41
	60	49	49	49	49	49	49	49	49	46	44	43	41
	70	46	46	46	46	46	46	46	46	46	44	43	41
	80	43	43	43	43	43	43	43	43	43	43	43	41
	90	41	41	41	41	41	41	41	41	41	41	41	41

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Portrait				
Table 59		Roof Angle: $0 < \theta \leq 7$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	98	98	98	96	88	81	75	70	66	64	62	58
	10	97	96	95	95	88	81	75	70	66	64	62	58
	20	80	80	80	80	80	79	75	70	66	64	62	58
	30	68	68	68	68	68	68	68	67	66	64	62	58
	40	59	59	59	59	59	59	59	59	59	59	59	58
	50	54	54	54	54	54	54	54	54	54	54	54	54
	60	49	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	85	77	73	70	64	59	55	51	48	48	45	43
	10	85	77	73	70	64	59	55	51	48	48	45	43
	20	80	77	73	70	64	59	55	51	48	48	45	43
	30	68	68	68	68	64	59	55	51	48	48	45	43
	40	59	59	59	59	59	59	55	51	48	48	45	43
	50	54	54	54	54	54	54	54	51	48	48	45	43
	60	49	49	49	49	49	49	49	49	48	48	45	43
	70	46	46	46	46	46	46	46	46	46	46	45	43
	80	43	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41	41
Zone 3	0	67	60	58	55	51	48	44	41	38	37	36	34
	10	67	60	58	55	51	48	44	41	38	37	36	34
	20	67	60	58	55	51	48	44	41	38	37	36	34
	30	67	60	58	55	51	48	44	41	38	37	36	34
	40	59	59	58	55	51	48	44	41	38	37	36	34
	50	54	54	54	54	51	48	44	41	38	37	36	34
	60	49	49	49	49	49	48	44	41	38	37	36	34
	70	46	46	46	46	46	46	44	41	38	37	36	34
	80	43	43	43	43	43	43	43	41	38	37	36	34
	90	41	41	41	41	41	41	41	41	38	37	36	34

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

Table 60 Mean Roof Height: $0 < h \leq 30$ ft Panel Orientation: Portrait
 Roof Angle: $0 < \theta \leq 7$ degrees
 Exposure Category: D

Roof Wind Zone	Ground Snow Load	Wind Speed (mph)										
		100	110	115	120	130	140	150	160	170	175	180
Zone 1	0	98	97	92	88	80	74	69	64	60	58	57
	10	96	95	92	88	80	74	69	64	60	58	57
	20	80	80	80	80	78	74	69	64	60	58	57
	30	68	68	68	68	68	68	67	64	60	58	57
	40	59	59	59	59	59	59	59	59	59	58	57
	50	54	54	54	54	54	54	54	54	54	54	53
	60	49	49	49	49	49	49	49	49	49	49	49
	70	46	46	46	46	46	46	46	46	46	46	46
	80	43	43	43	43	43	43	43	43	43	43	43
	90	41	41	41	41	41	41	41	41	41	41	41
Zone 2	0	77	70	67	64	58	54	50	48	44	43	42
	10	77	70	67	64	58	54	50	48	44	43	42
	20	77	70	67	64	58	54	50	48	44	43	42
	30	68	68	67	64	58	54	50	48	44	43	42
	40	59	59	59	59	58	54	50	48	44	43	42
	50	54	54	54	54	54	54	50	48	44	43	42
	60	49	49	49	49	49	49	49	48	44	43	42
	70	46	46	46	46	46	46	46	46	44	43	42
	80	43	43	43	43	43	43	43	43	43	42	39
	90	41	41	41	41	41	41	41	41	41	41	39
Zone 3	0	61	55	53	50	46	43	40	37	35	34	33
	10	61	55	53	50	46	43	40	37	35	34	33
	20	61	55	53	50	46	43	40	37	35	34	33
	30	61	55	53	50	46	43	40	37	35	34	33
	40	59	55	53	50	46	43	40	37	35	34	33
	50	54	54	53	50	46	43	40	37	35	34	33
	60	49	49	49	49	46	43	40	37	35	34	33
	70	46	46	46	46	46	43	40	37	35	34	33
	80	43	43	43	43	43	43	40	37	35	34	33
	90	41	41	41	41	41	41	40	37	35	34	33

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Portrait				
Table 61		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: B											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	98	98	98	98	98	98	93	87	81	79	77	72
	10	93	91	90	89	87	85	83	81	79	78	77	72
	20	73	73	73	73	73	72	71	69	68	68	67	66
	30	62	62	62	62	62	62	62	62	61	60	60	59
	40	54	54	54	54	54	54	54	54	54	54	54	54
	50	49	49	49	49	49	49	49	49	49	49	49	49
	60	45	45	45	45	45	45	45	45	45	45	45	45
	70	42	42	42	42	42	42	42	42	42	42	42	42
	80	40	40	40	40	40	40	40	40	40	40	40	40
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 2	0	98	92	88	84	77	71	67	62	59	57	55	52
	10	93	91	88	84	77	71	67	62	59	57	55	52
	20	73	73	73	73	73	71	67	62	59	57	55	52
	30	62	62	62	62	62	62	62	62	59	57	55	52
	40	54	54	54	54	54	54	54	54	54	54	54	52
	50	49	49	49	49	49	49	49	49	49	49	49	49
	60	45	45	45	45	45	45	45	45	45	45	45	45
	70	42	42	42	42	42	42	42	42	42	42	42	42
	80	40	40	40	40	40	40	40	40	40	40	40	40
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 3	0	81	74	70	67	62	57	53	50	48	46	44	42
	10	81	74	70	67	62	57	53	50	48	46	44	42
	20	73	73	70	67	62	57	53	50	48	46	44	42
	30	62	62	62	62	62	57	53	50	48	46	44	42
	40	54	54	54	54	54	54	53	50	48	46	44	42
	50	49	49	49	49	49	49	49	49	48	46	44	42
	60	45	45	45	45	45	45	45	45	45	45	44	42
	70	42	42	42	42	42	42	42	42	42	42	42	42
	80	40	40	40	40	40	40	40	40	40	40	40	40
	90	37	37	37	37	37	37	37	37	37	37	37	37

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft							Panel Orientation: Portrait				
Table 62		Roof Angle: $7 < \theta \leq 27$ degrees											
		Exposure Category: C											
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)											
		100	110	115	120	130	140	150	160	170	175	180	190
Zone 1	0	98	98	98	98	90	84	78	73	68	66	64	61
	10	90	87	86	85	83	80	78	73	68	66	64	61
	20	73	73	72	72	70	69	67	66	64	64	63	61
	30	62	62	62	62	62	61	60	59	58	57	57	56
	40	54	54	54	54	54	54	54	54	53	53	52	51
	50	49	49	49	49	49	49	49	49	49	49	49	48
	60	45	45	45	45	45	45	45	45	45	45	45	45
	70	42	42	42	42	42	42	42	42	42	42	42	42
	80	40	40	40	40	40	40	40	40	40	40	40	40
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 2	0	85	77	74	70	65	60	56	52	49	48	46	44
	10	85	77	74	70	65	60	56	52	49	48	46	44
	20	73	73	72	70	65	60	56	52	49	48	46	44
	30	62	62	62	62	62	60	56	52	49	48	46	44
	40	54	54	54	54	54	54	54	52	49	48	46	44
	50	49	49	49	49	49	49	49	49	49	48	46	44
	60	45	45	45	45	45	45	45	45	45	45	45	44
	70	42	42	42	42	42	42	42	42	42	42	42	42
	80	40	40	40	40	40	40	40	40	40	40	40	40
	90	37	37	37	37	37	37	37	37	37	37	37	37
Zone 3	0	68	62	59	57	52	48	45	42	40	38	37	35
	10	68	62	59	57	52	48	45	42	40	38	37	35
	20	68	62	59	57	52	48	45	42	40	38	37	35
	30	62	62	59	57	52	48	45	42	40	38	37	35
	40	54	54	54	54	52	48	45	42	40	38	37	35
	50	49	49	49	49	49	48	45	42	40	38	37	35
	60	45	45	45	45	45	45	45	42	40	38	37	35
	70	42	42	42	42	42	42	42	42	40	38	37	35
	80	40	40	40	40	40	40	40	40	40	38	37	35
	90	37	37	37	37	37	37	37	37	37	37	37	35

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft										Panel Orientation: Portrait		
		Roof Angle: $7 < \theta \leq 27$ degrees												
		Exposure Category: D												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	98	98	94	90	83	77	71	67	63	61	59	56	
	10	88	85	84	82	80	77	71	67	63	61	59	56	
	20	73	72	71	70	69	67	65	64	62	61	59	56	
	30	62	62	62	62	61	60	59	58	56	56	55	54	
	40	54	54	54	54	54	54	54	53	52	51	51	50	
	50	49	49	49	49	49	49	49	49	48	48	48	48	
	60	45	45	45	45	45	45	45	45	45	45	45	44	
	70	42	42	42	42	42	42	42	42	42	42	42	42	
	80	40	40	40	40	40	40	40	40	40	40	40	40	
	90	37	37	37	37	37	37	37	37	37	37	37	37	
Zone 2	0	78	71	67	65	59	55	51	48	45	44	43	40	
	10	78	71	67	65	59	55	51	48	45	44	43	40	
	20	73	71	67	65	59	55	51	48	45	44	43	40	
	30	62	62	62	62	59	55	51	48	45	44	43	40	
	40	54	54	54	54	54	54	51	48	45	44	43	40	
	50	49	49	49	49	49	49	49	48	45	44	43	40	
	60	45	45	45	45	45	45	45	45	45	44	43	40	
	70	42	42	42	42	42	42	42	42	42	42	42	40	
	80	40	40	40	40	40	40	40	40	40	40	40	40	
	90	37	37	37	37	37	37	37	37	37	37	37	37	
Zone 3	0	63	57	54	52	48	44	41	39	36	35	34	32	
	10	63	57	54	52	48	44	41	39	36	35	34	32	
	20	63	57	54	52	48	44	41	39	36	35	34	32	
	30	62	57	54	52	48	44	41	39	36	35	34	32	
	40	54	54	54	52	48	44	41	39	36	35	34	32	
	50	49	49	49	49	48	44	41	39	36	35	34	32	
	60	45	45	45	45	45	44	41	39	36	35	34	32	
	70	42	42	42	42	42	42	41	39	36	35	34	32	
	80	40	40	40	40	40	40	40	39	36	35	34	32	
	90	37	37	37	37	37	37	37	37	36	35	34	32	

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft										Panel Orientation: Portrait		
		Roof Angle: $27 < \theta \leq 45$ degrees												
		Exposure Category: B												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	98	97	95	92	87	83	78	75	71	70	68	65	
	10	89	87	85	84	81	78	75	73	70	69	68	65	
	20	77	75	74	73	71	69	67	65	64	63	62	60	
	30	68	67	66	66	64	63	61	60	59	58	57	56	
	40	60	60	60	60	59	58	57	56	54	54	53	52	
	50	54	54	54	54	54	54	53	52	51	51	50	49	
	60	50	50	50	50	50	50	50	49	48	48	48	48	
	70	48	48	48	48	48	48	48	48	46	46	45	45	
	80	44	44	44	44	44	44	44	44	44	44	43	43	
	90	42	42	42	42	42	42	42	42	42	42	42	41	
Zone 2	0	98	97	95	92	87	83	78	73	69	67	65	62	
	10	89	87	85	84	81	78	75	73	69	67	65	62	
	20	77	75	74	73	71	69	67	65	64	63	62	60	
	30	68	67	66	66	64	63	61	60	59	58	57	56	
	40	60	60	60	60	59	58	57	56	54	54	53	52	
	50	54	54	54	54	54	54	53	52	51	51	50	49	
	60	50	50	50	50	50	50	50	49	48	48	48	48	
	70	48	48	48	48	48	48	48	48	46	46	45	45	
	80	44	44	44	44	44	44	44	44	44	44	43	43	
	90	42	42	42	42	42	42	42	42	42	42	42	41	
Zone 3	0	98	97	95	92	87	83	78	73	69	67	65	62	
	10	89	87	85	84	81	78	75	73	69	67	65	62	
	20	77	75	74	73	71	69	67	65	64	63	62	60	
	30	68	67	66	66	64	63	61	60	59	58	57	56	
	40	60	60	60	60	59	58	57	56	54	54	53	52	
	50	54	54	54	54	54	54	53	52	51	51	50	49	
	60	50	50	50	50	50	50	50	49	48	48	48	48	
	70	48	48	48	48	48	48	48	48	46	46	45	45	
	80	44	44	44	44	44	44	44	44	44	44	43	43	
	90	42	42	42	42	42	42	42	42	42	42	42	41	

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft										Panel Orientation: Portrait		
		Roof Angle: $27 < \theta \leq 45$ degrees												
		Exposure Category: C												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	93	87	84	82	77	73	69	65	62	60	59	56	
	10	84	81	79	77	74	71	68	65	62	60	59	56	
	20	73	71	70	69	67	64	62	60	58	57	56	55	
	30	66	64	63	63	61	59	57	56	54	53	53	51	
	40	60	59	58	58	56	55	54	52	51	50	50	48	
	50	54	54	54	54	53	52	50	49	48	48	48	46	
	60	50	50	50	50	50	49	48	48	46	45	45	44	
	70	48	48	48	48	48	46	46	45	44	43	43	42	
	80	44	44	44	44	44	44	44	43	42	42	41	41	
	90	42	42	42	42	42	42	42	41	40	40	40	39	
Zone 2	0	93	87	84	82	76	71	66	62	58	56	55	52	
	10	84	81	79	77	74	71	66	62	58	56	55	52	
	20	73	71	70	69	67	64	62	60	58	56	55	52	
	30	66	64	63	63	61	59	57	56	54	53	53	51	
	40	60	59	58	58	56	55	54	52	51	50	50	48	
	50	54	54	54	54	53	52	50	49	48	48	48	46	
	60	50	50	50	50	50	49	48	48	46	45	45	44	
	70	48	48	48	48	48	46	46	45	44	43	43	42	
	80	44	44	44	44	44	44	44	43	42	42	41	41	
	90	42	42	42	42	42	42	42	41	40	40	40	39	
Zone 3	0	93	87	84	82	76	71	66	62	58	56	55	52	
	10	84	81	79	77	74	71	66	62	58	56	55	52	
	20	73	71	70	69	67	64	62	60	58	56	55	52	
	30	66	64	63	63	61	59	57	56	54	53	53	51	
	40	60	59	58	58	56	55	54	52	51	50	50	48	
	50	54	54	54	54	53	52	50	49	48	48	48	46	
	60	50	50	50	50	50	49	48	48	46	45	45	44	
	70	48	48	48	48	48	46	46	45	44	43	43	42	
	80	44	44	44	44	44	44	44	43	42	42	41	41	
	90	42	42	42	42	42	42	42	41	40	40	40	39	

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"

Rail Spans for Quick Mount PV QRail Standard System

		Mean Roof Height: $0 < h \leq 30$ ft										Panel Orientation: Portrait		
Table 66		Roof Angle: $27 < \theta \leq 45$ degrees												
		Exposure Category: D												
Roof Wind Zone	Ground Snow Load	Wind Speed (mph)												
		100	110	115	120	130	140	150	160	170	175	180	180	190
Zone 1	0	88	82	79	77	72	68	64	61	58	56	55	55	52
	10	81	78	76	74	71	68	64	61	58	56	55	55	52
	20	71	69	68	66	64	62	60	57	55	54	53	53	52
	30	64	63	62	61	59	57	55	54	52	51	50	49	49
	40	59	58	57	56	55	53	52	50	49	48	48	48	46
	50	54	54	53	53	51	50	49	48	48	46	45	45	44
	60	50	50	50	50	49	48	48	46	44	44	43	43	42
	70	48	48	48	48	46	45	44	44	43	42	42	42	41
	80	44	44	44	44	44	43	43	42	41	41	40	39	39
	90	42	42	42	42	42	42	41	40	39	39	39	39	38
Zone 2	0	88	82	79	76	70	65	61	57	53	52	50	50	48
	10	81	78	76	74	70	65	61	57	53	52	50	50	48
	20	71	69	68	66	64	62	60	57	53	52	50	50	48
	30	64	63	62	61	59	57	55	54	52	51	50	48	48
	40	59	58	57	56	55	53	52	50	49	48	48	48	46
	50	54	54	53	53	51	50	49	48	48	46	45	45	44
	60	50	50	50	50	49	48	48	46	44	44	43	43	42
	70	48	48	48	48	46	45	44	44	43	42	42	42	41
	80	44	44	44	44	44	43	43	42	41	41	40	39	39
	90	42	42	42	42	42	42	41	40	39	39	39	39	38
Zone 3	0	88	82	79	76	70	65	61	57	53	52	50	50	48
	10	81	78	76	74	70	65	61	57	53	52	50	50	48
	20	71	69	68	66	64	62	60	57	53	52	50	50	48
	30	64	63	62	61	59	57	55	54	52	51	50	48	48
	40	59	58	57	56	55	53	52	50	49	48	48	48	46
	50	54	54	53	53	51	50	49	48	48	46	45	45	44
	60	50	50	50	50	49	48	48	46	44	44	43	43	42
	70	48	48	48	48	46	45	44	44	43	42	42	42	41
	80	44	44	44	44	44	43	43	42	41	41	40	39	39
	90	42	42	42	42	42	42	41	40	39	39	39	39	38

Notes:

- Tables are based on critical rail span for load combinations as specified in chapter 2 of the ASCE 7-10 and allowable design loads per the 2015 Aluminum Design Manual.
- Panels are assumed to be in portrait orientation with a maximum length of 80"