


SP80P / SP85P



POLY-CRISTALLINE SOLAR MODULE 12V

36 CELLS 156x97mm

With a power output ranging from 10W up to 150W our off-grid solar panels are very versatile, and can be used on camping vans, mountain huts, boats and for every other off-grid application.

Our off-grid panels also ensure high performances even when it comes to generating electricity at low voltage (12V), and are therefore particularly suitable for public lighting.

These panels represent the ideal choice for installations in secluded or isolated areas.



High reliability with guaranteed 0 to +5W power output tolerance



30 Year Linear Power Warranty
12 Year Product Warranty



Excellent performance under different light conditions



IP65 JUNCTION BOX
Able to withstand the most varied atmospheric conditions



Passing mechanical load test of 5400 Pa to withstand heavier snow load and 2400 Pa to withstand wind pressure



Compact and ultra-light aluminum frame with 35mm thickness to handle the panel in an easier way



ELECTRICAL CHARACTERISTICS (STC)*


| | SP80P | SP85P |
|-------------------------------------|--------|--------|
| Nominal Output (Pmax) [W] | 80 | 85 |
| Flash Test Power Classification [W] | 0 / +5 | 0 / +5 |
| Voltage at Pmax (Vmp) [V] | 17.78 | 17.78 |
| Current at Pmax (Imp) [A] | 4.50 | 4.78 |
| Open Circuit Voltage (Voc) [V] | 21.33 | 21.33 |
| Short Circuit Current (Isc) [A] | 5.03 | 5.35 |
| Maximum System Voltage [V] | 1000 | 1000 |
| Maximum Series Fuse Rating [A] | 14.69 | 15.60 |
| Cell Efficiency [%] | 12.48 | 13.26 |

STC* (Standard Test Condition): Irradiance 1000W/m², Module Temperature 25°C, Air Mass 1.5

MECHANICAL CHARACTERISTICS

| | |
|--------------|---|
| Solar Cells | 36(4x9) poly-crystalline cells 156x97 mm |
| Font Cover | 3.2 mm thick, low iron tempered glass |
| Back Cover | TPT (Tedlar-PET-Tedlar) |
| Encapsulant | EVA (Ethylene vinyl acetate) |
| Frame | Anodized aluminium alloy, double wall |
| Diodes | 3 Bypass diodes serviceable |
| Junction Box | IP65 rated |
| Connector | MC4 or compatible connector |
| Cables | Length: 900 mm / Section: 4.0 mm ² |
| Dimensions | 951 x 674 x 35 mm |
| Weight | 7.15 kg |
| Max. Load | Certified to 5400 Pa |

DIMENSIONS



TEMPERATURE CHARACTERISTICS

| | |
|---------------------------------|---------------|
| NOCT** | 45±2 °C |
| Temperature Coefficient of Pmax | -0.43 %/°C |
| Temperature Coefficient of Voc | -0.32 %/°C |
| Temperature Coefficient of Isc | 0.047 %/°C |
| Operating Temperature | -40°C ~ +85°C |

NOCT**: Nominal Operation Cell Temperature Sun 800W/m²; Air 20°C; Wind speed 1m/s

PACKING CONFIGURATION

| | |
|-------------------|-------------------|
| Box dimensions | 970 x 685 x 45 mm |
| Pieces per pallet | 1 pcs |
| Weight | 7.3 kg |

* Pallets can be stacked up to two

CURRENT / VOLTAGE CHARACTERISTICS

