



Product availability: Stock - Normally stocked in distribution facility
Price*: 1748.00 USD



Main

Product or component typeproduct or component type	Single Throw Safety Switch
Line Rated CurrentLine Rated Current	200 A
Product certification-product certifications	UL listed
NEMA degree of protectionNEMA degree of protection	NEMA 3R galvanized steel
Device compositiondevice composition	Neutral (factory installed)
Disconnecter device typedisconnector device type	Fusible disconnect
Short-circuit currentshort-circuit current	10 kA H or K 200 kA R, J or L
Device mountingdevice mounting	Surface
Number of polesnumber of poles	3
Electrical connection-electrical connection	Lugs
Series nameseries name	Heavy duty
System VoltageSystem Voltage	250 V DC 240 V AC
AWG gaugeAWG gauge	AWG 6...250 kcmil (copper or aluminium)

Ordering and shipping details

CategoryCategory	00009 - H&HU, 2&3P, N3R,30-200A
Discount ScheduleDiscount Schedule	DE1
GTINGTIN	00785901480594
Nbr. of units in pkg.Nbr. of units in pkg.	1
ReturnabilityReturnability	Y
Country of originCountry of origin	US

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative.

Offer Sustainability

Sustainable offer status	Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	RoHS (date code: YY-WW)	Compliant since 1313; Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	REACH	Reference not containing SVHC above the threshold
Product environmental profile	Product environmental profile	Available
Product end of life instructions	Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	Warranty period	18 months
-----------------	-----------------	-----------