

“Stay Connected” with



Solar Power Components

a PennEngineering® Company




HEYClip™ Stainless Steel SunRunner® 4-2 and 4-2U Cable Clips


For Oval Micro-Inverter Cables

- Designed to hold Micro-Inverter oval cables .250" (6,3 mm) x .385" (9,8 mm).
- Constructed from heat treated 410 stainless steel for excellent strength and corrosion protection for outdoor exposure.
- Smooth clip edges prevent damage to cable insulation.
- “S” hook clip design will fit a wide variety of extruded aluminum profiles.
- SunRunner 4-2 is designed for solar mounting frames such as the ones used by with Everest, SnapNrack and similar extrusions.
- SunRunner 4-2U features a shorter S hook for Unirac, IronRidge and similar frame profiles.
- Neatly dresses cables along mounting frame channels from .080" (2,5 mm) to .250" (6,4 mm) thick.
- See page 1-11 for typical rack profile applications.


| CHANNEL THICKNESS CLAMPING RANGE | | | | WIRE CAPACITY | | PART NO. | DESCRIPTION | FOOTPRINT | | REAR TAB LENGTH | |
|----------------------------------|---------|---------|---------|---------------|------------|----------|----------------------------|------------|-------------|-----------------|------|
| Minimum | Maximum | Minimum | Maximum | in. | mm. | | | in. | mm. | in. | mm. |
| SunRunner 4-2 | | | | | | | | | | | |
| .08 | 2,0 | .25 | 6,4 | .25 x 1,00 | 6,4 x 25,4 | S6504 | SunRunner 4-2 100 Pack | .50 x 1,34 | 12,7 x 34,0 | .84 | 21,3 |
| | | | | | | | S6544 | | | | |
| SunRunner 4-2U | | | | | | | | | | | |
| .25 | 6,4 | .25 | 6,4 | .25 x 1,00 | 6,4 x 25,4 | S6505 | SunRunner 4-2U 100 Pack | .50 x 1,34 | 12,7 x 34,0 | .38 | 9,7 |
| | | | | | | | S6545 | | | | |



SunRunner 4-2



SunRunner 4-2U



Quick Specs

Material .020" thick 410 stainless steel
 Certifications Certified by UL for Compliance with both Canadian and US Requirements under File E54523
 Temperature Range -40°F (-40°C) to 572°F (300°C)