AGM 12/270 (group Super 8D)



Product code: 62002700



AGM batteries

In AGM batteries, the electrolyte (mixture of water and sulphuric acid) is largely absorbed in glass fibre. This type of battery is entirely maintenance-free and there is no gas formation with normal use. Not requiring any ventilation, these batteries can be installed anywhere.

Their construction gives a very fast discharge at very high currents so AGM batteries are ideal for systems that require high currents (for instance when starting an engine). The battery poles can be unscrewed and this type of battery can be combined with every standard battery terminal.

- · Excellent starter function.
- · Perfect upgrade for wet lead acid batteries.
- $\cdot~$ Same initial power surge in an AGM 12/90 Ah as 180 Ah wet lead-acid battery.
- · Glass-fibre technology ensures low internal resistance.
- \cdot Use of thicker plates extends lifespan.
- · Also for medium cyclical use.
- · Two-year warranty.



Specifications

General specifications

Nominal battery voltage 12 V Nominal battery capacity C20 (battery capacity at a discharge 270 Ah

time of 20 hours, till 10.5 V per battery)

Max. charge current 76.5 Ah

Battery terminals M8

Max. outer dimensions (incl. terminals/grip handles), lxwxh 522 x 268 x 226 mm

20.6 x 10.6 x 8.9 inch

Weight 73 kg

160.9 lb

Technical specifications

 CCA to DIN
 750 A

 CCA to SAE
 1200 A

