



PVX-6720T, 2V



PVX-2240T, 6V



PVX-2580L, 12V

Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell

Sun Xtender® Part Number	Volt	Industry Reference	Overall Dimensions Inches (mm)			Unit Weight LB / KG	1 Hour Rate	2 Hour Rate	4 Hour Rate	8 Hour Rate	24 Hour Rate	100 Hour Rate
			Length	Width	Height							
PVX-340T	12	U1	7.71 (196)	5.18 (132)	6.89 (175)	25/11.4	21	27	28	30	34	37
PVX-420T	12	U1 Tall	7.71 (196)	5.18 (132)	8.05 (204)	30/13.6	26	33	34	36	42	44
PVX-490T	12	22NF	8.99 (228)	5.45 (138)	8.82 (224)	36/16.4	31	39	40	43	49	54
PVX-560T	12	22NF	8.99 (228)	5.45 (138)	8.82 (224)	40/18.2	36	45	46	49	56	62
PVX-690T	12	24	10.22 (259)	6.60 (168)	8.93 (227)	51/23.2	42	53	55	60	69	78
PVX-840T	12	24	10.22 (259)	6.60 (168)	8.93 (227)	57/25.9	52	66	68	74	84	96
PVX-890T	12	31	12.90 (328)	6.75 (172)	8.96 (228)	62/28.2	55	70	72	79	89	100
PVX-1040HT	12	27	13.12 (333)	6.60 (168)	8.93 (227)	63/28.6	65	82	85	93	104	118
PVX-1040T	12	27	12.01 (305)	6.60 (168)	8.93 (227)	63/28.6	65	82	85	93	104	118
PVX-1080T	12	31	12.90 (328)	6.75 (172)	8.96 (228)	65/29.5	68	86	88	97	108	124
<b>NEW »</b> PVX-1180T	12	31	12.90 (328)	6.75 (171)	8.96 (228)	72/32.7	72	92	95	104	118	135
<b>NEW »</b> PVX-1290T	12	31	12.90 (328)	6.75 (171)	8.96 (228)	75/34	79	100	103	113	129	146
<b>NEW »</b> PVX-1530T	12	30H	13.46 (342)	6.77 (172)	11.95 (304)	97/44.0	95	120	124	136	153	176
PVX-2120L	12	4D	20.76 (527)	8.70 (221)	9.77 (248)	127/57.6	136	172	176	194	212	250
PVX-2580L	12	8D	20.76 (527)	10.89 (277)	9.77 (248)	159/72.1	165	209	214	236	258	300
PVX-1030T	6	24	10.21 (259)	6.60 (168)	8.92 (227)	42/19.1	65	82	85	93	103	118
PVX-1380T	6	24	10.21 (259)	6.60 (168)	8.92 (227)	51/23.2	84	106	110	120	138	155
PVX-2240T	6	GC2	10.28 (261)	7.06 (179)	9.92 (252)	67/30.4	143	180	185	204	224	260
<b>NEW »</b> PVX-2560T	6	31	12.90 (328)	6.75 (171)	8.96 (228)	75/34	158	200	206	226	256	292
PVX-3050T	6	GC2 Tall	10.28 (261)	7.06 (179)	13.02 (331)	91/41.3	190	245	270	280	305	354
<b>NEW »</b> PVX-4050HT	6	L-16	11.64 (296)	6.95 (177)	15.73 (399)	120/54.4	266	345	360	376	405	443
PVX-5040T <sup>1</sup>	2	24	10.21 (259)	6.60 (168)	8.93 (227)	57/25.9	312	396	408	444	504	574
PVX-5340T <sup>1</sup>	2	31	12.90 (328)	6.75 (171)	8.96 (228)	64/29.0	330	420	432	474	534	604
PVX-6240T <sup>1</sup>	2	27	12.01 (305)	6.60 (168)	8.93 (227)	65/29.5	390	492	510	558	624	710
PVX-6480T <sup>1</sup>	2	31	12.90 (328)	6.75 (171)	8.96 (228)	67/30.5	408	516	528	582	648	746
PVX-6720T <sup>1</sup>	2	GC2	10.28 (261)	7.06 (179)	9.92 (252)	70/31.8	429	540	555	612	672	780
<b>NEW »</b> PVX-7680T <sup>1</sup>	2	31	12.90 (328)	6.75 (171)	8.96 (228)	75/34	474	600	618	678	768	876
PVX-9150T <sup>1</sup>	2	GC2 Tall	10.28 (261)	7.06 (179)	13.02 (331)	94/42.6	570	735	810	840	915	1062
<b>NEW »</b> PVX-12150HT <sup>1</sup>	2	L-16	11.64 (296)	6.95 (177)	15.73 (399)	124/56.2	798	1035	1080	1128	1215	1329

<sup>1</sup> 4 terminal battery

For full specifications, refer to our website, [www.sunxtender.com](http://www.sunxtender.com)  
 Specifications subject to change without notice. Never install batteries in an airtight or sealed enclosure. Insure installation is adequately ventilated.

