



samlexamerica®

2750W



DC-AC Inverter Modified Sine Wave

Model
PSE-24275A
24 VDC
120 VAC

Design Features

- High efficiency PWM design
- LED bar graphs indicate input voltage, input current and output power
- Temperature controlled cooling fan
- Low input voltage warning alarm
- Optional remote operation with Samlex Model RC-15 remote control (sold separately)
- Protections: high/low DC input voltage, over temperature and over load shut down
- High output power surge

2 YEAR WARRANTY

		MODEL NO.	PSE-24275A
OUTPUT		OUTPUT VOLTAGE	120VAC +5% / - 10%
		OUTPUT FREQUENCY	60Hz ± 5%
		OUTPUT VOLTAGE WAVEFORM	Modified Sine Wave
		MAX. CONTINUOUS ACTIVE POWER OUTPUT (POWER FACTOR = 1)	2750W*
		MAX. ACTIVE SURGE POWER OUTPUT (< 2 SEC, POWER FACTOR =1)	4500W*
INPUT		PEAK EFFICIENCY	85% to 90%
		DC INPUT VOLTAGE	24V Battery System (> 21VDC to < 33VDC)
		MAXIMUM DC INPUT CURRENT	< 180A
		NO LOAD CURRENT DRAW	600mA
MONITORING & INDICATIONS		DC INPUT VOLTAGE, VOLTS	Colored, 10 Level LED Bar Graph
		DC INPUT CURRENT, AMPS & ASSOCIATED OUTPUT POWER, WATTS	Colored, 10 Level LED Bar Graph
		OVER TEMPERATURE	Red LED + Buzzer Alarm
		OVERLOAD	Red LED
PROTECTIONS		LOW DC INPUT VOLTAGE	Buzzer Alarm
		COOLING	Temperature Controlled Fan
		OVER LOAD / SHORT CIRCUIT	<ul style="list-style-type: none"> • Shutdown if output power > Continuous / Surge Ratings • Manual Reset: Switch OFF, wait for 3 min and Switch ON
		OVER TEMPERATURE	<ul style="list-style-type: none"> • Shut Down when temperature of internal hot spot > threshold • Automatic reset when unit cools down
		HIGH DC INPUT VOLTAGE	<ul style="list-style-type: none"> • Shut down when DC Input Voltage > 33VDC • Auto reset when voltage drops below 33VDC
		LOW DC INPUT VOLTAGE	<ul style="list-style-type: none"> • Shut down when DC Input Voltage < 20VDC • Auto reset when voltage rises to > 21.3VDC
		LOW DC INPUT VOLTAGE ALARM	<ul style="list-style-type: none"> • Buzzer alarm when DC Input Voltage < 21VDC • Auto reset when voltage rises > 21VDC
INPUT & OUTPUT CONNECTIONS		INTERNAL DC SIDE FUSES	Automotive Type ATC, 32V - 180A (15A x 12 pcs.)
		DC INPUT CONNECTIONS	5/16" bolt and nut, 18 TPI 3 x AWG #10 wires in covered pocket for hard wiring to panel / 2 Knock Outs (Hole diameter 22 mm / 0.87") for 3/8" fitting for cable entry / Plate with NEMA5-15R outlet and 15A Breaker for front panel outlet
		AC OUTPUT CONNECTIONS	
		REMOTE CONTROL CONNECTION	6P6C Modular Jack
ENVIRONMENTAL CONDITIONS		REMOTE CONTROL (OPTIONAL)	Wired Remote Control with 15 ft cable – Model RC-15
		OPERATING TEMPERATURE	0°C to 40°C / 32°F to 104°F
		STORAGE TEMPERATURE	-10°C to 65°C / 14°F to 149°F
GENERAL		HUMIDITY	85% RH, Non Condensing
		DIMENSIONS (W x D x H)	205 x 495 x 160 mm / 8.07 x 19.49 x 6.30 inches
		DIMENSIONS (W x D x H)	7.35 kg. / 16.2 lbs.

NOTE: * This is the Active Power output for resistive type of load with Power Factor = 1. For reactive loads, the rating will be reduced by the Power Factor of particular type of load (0.8 to 0.6)

NOTE: Specifications are subject to change without notice

12001-PSE-24275A-0414