


NEMA TYPE 3R  
ILLUSTRATED ▲



| TERMINAL LUGS ‡ |           |           |      |
|-----------------|-----------|-----------|------|
| AMPERES         | MAX. WIRE | MIN. WIRE | TYPE |
| 100             | 1/0 AWG   | #12 AWG   | AL   |
|                 | 1/0 AWG   | #14 AWG   | CU   |

| KNOCKOUTS |              |    |          |    |
|-----------|--------------|----|----------|----|
| SYMBOL    | CONDUIT SIZE |    | DIAMETER |    |
|           | IN           | MM | IN       | MM |
| A         | .50          | 13 | .88      | 22 |
| B         | .75          | 19 | 1.13     | 29 |
| C         | 1.00         | 25 | 1.38     | 35 |
| D         | 1.25         | 32 | 1.75     | 45 |
| E         | 1.50         | 38 | 2.00     | 51 |
| F         | 2.00         | 51 | 2.50     | 64 |

DUAL DIMENSIONS: INCHES  
MILLIMETERS

NOTES:  
FINISH - GRAY BAKED ENAMEL  
UL LISTED - FILE E-2875  
ALL NEUTRALS - INSULATED GROUNDABLE  
SUITABLE FOR USE AS SERVICE EQUIPMENT  
SHORT CIRCUIT CURRENT RATINGS:

- 10,000 AMPERES WITH CLASS H OR K FUSES
- 100,000 AMPERES WITH CLASS R FUSES HAVING CLASS R REJECTION KITS INSTALLED.
- WHEN MOUNTING THESE SWITCHES, ALLOW 4.00/[102] MIN. CLEARANCE BETWEEN ENCLOSURES FOR OPENING OF SIDE HINGED DOOR.
- ▲ TOP OF NEMA TYPE 3R DEVICES HAVE PROVISIONS FOR MAXIMUM 2.50/[64] BOLT-ON HUB.
- \* FOR CORNER GROUNDED DELTA SYSTEMS ONLY.
- REQUIRES FIELD INSTALLATION OF EQUIPMENT GROUNDING KIT GTK0610 WHEN USED AS SERVICE EQUIPMENT.
- ‡ LUGS SUITABLE FOR 60°C OR 75°C CONDUCTORS.

| CATALOG NUMBER | VOLTAGE RATINGS | WIRING DIAG. | HORSEPOWER RATINGS |      |      |      |
|----------------|-----------------|--------------|--------------------|------|------|------|
|                |                 |              | 240VAC             |      |      |      |
|                |                 |              | STD.               |      | MAX. |      |
|                |                 |              | 1Ø                 | 3Ø   | 1Ø   | 3Ø   |
| D223NRB        | 240VAC          | A            | 7 1/2              | 15 * | 15   | 30 * |
| D323NRB        | 240VAC          | B            | 7 1/2              | 15   | 15   | 30   |
| DU323RB ■      | 240VAC          | C            | -                  | -    | 15   | 30   |

GENERAL DUTY SAFETY SWITCHES  
VISIBLE BLADE TYPE  
100 AMPERE  
ENCLOSURE - NEMA TYPE 3R RAINPROOF



DWG# 1865  
NO.