

## 60K-3P-480V-N

**Spec Sheet** 



| Solar In   | lar Input Power 78,000W                  |  |
|--|--|--|
| Max Allowed PV Power                             | 78,000W                                  |  |
| Max PV Power Delivered to Battery & AC Outputs   | 60,000W                                  |  |
| Max DC Voltage (Voc)                             | 1,000V @ 36A                             |  |
| MPPT Voltage Range                               | 200-850V                                 |  |
| Starting Voltage                                 | 180V                                     |  |
| Number of MPPT                                   | 4  |  |
| Max Solar Strings Per MPPT                       | 2  |  |
| Max DC Current per MPPT (Self Lim-<br>iting)     | 36A                                      |  |
| Max AC Coupled Input (Micro/String<br>Inverters) | 277V x 150A x 3 = 125KVA<br>with no PVdc |  |

## Output Power 60kW On-Grid & Off-Grid Protections & Certifications AC

| Connections                                   | 277V / 480V Three Phase                 |
|---|---|
| Continuous AC Power with PV                   | 60,000W   72.2A (480V)                  |
| Continuous AC Power from Batteries            | 60,000W   72.2A (480V) TBD              |
| Surge AC Power   7 sec                        | 120,000VA   144.4A x 277V x<br>3        |
| Parallel Stacking                             | Yes - Up to 12                          |
| Frequency                                     | 60/50Hz                                 |
| Continuous AC Power with Grid or<br>Generator | 102,000W   160A L-N (277V)              |
| CEC Efficiency                                | 96.5% (Peak 97.5%)                      |
| Idle Consumption Typical—No Load              | TBD                                     |
| Sell Back Power Modes                         | Limited to Household/Fully<br>Grid-Tied |
| Design (DC to AC)                             | Transformerless DC                      |
| Response Time (Grid-Tied to Off-Grid)         | 5ms                                     |
| Power Factor                                  | +/- 0.8 - 1.0                           |

| Battery (optional) Output Power 60,000W     |                         |
|---|-------------------------|
| Type   Number of Inputs                     | Li-Ion   2 Inputs       |
| Nominal DC Input                            | >600V                   |
| Capacity                                    | 50 — 9,900Ah            |
| Voltage Range                               | 160V ~ 800V             |
| Continuous Battery Charging Output          | 100A (50A Per Input)    |
| Charging Curve                              | 3-Stage w/ Equalization |
| Grid to Batt Charging Efficiency            | 96.0%                   |
| External Temperature Sensor                 | Included                |
| Current Shunt for Accurate % SOC            | Integrated              |
| External Gen Start Based on Voltage or %SOC | Integrated              |
| Communication to Lithium Battery            | CanBus & RS485          |

| General                                      |                             |  |
|--|-----------------------------|--|
| Dimensions (H x W x D)                       | 35.2" x 20.8" x<br>11.6"    |  |
| Weight                                       | 172 lbs                     |  |
| Enclosure                                    | IP65 / NEMA 3R              |  |
| Ambient Temperature                          | -40~60°C, >45°C<br>Derating |  |
| Installation Style                           | Wall-Mounted                |  |
| Wi-Fi & LAN Communication                    | Included                    |  |
| Standard Warranty (verified by HALT Testing) | 10 years                    |  |

| Electronics Certified Safety by SGS Labs to NEC<br>& UL Specs - NEC 690.4B & NEC 705.4/6                            | pending                     |
|---|-----------------------------|
| Grid Sell Back — UL1741-2010/2018, IEE-<br>E1547a-2003/2014, FCC 15 Class B, UL1741SB,<br>CA Rule 21, HECO Rule 14H | pending                     |
| PV DC Disconnect Switch — NEC 240.15  | Integrated                  |
| Ground Fault Detection — NEC 690.5  | Integrated                  |
| PV Rapid Shutdown Control — NEC 690.12  | Integrated                  |
| PV Arc Fault Detection — NEC 690.11   | Integrated                  |
| PV Input Lightning Protection   | Integrated                  |
| PV String Input Reverse Polarity Protection   | Integrated                  |
| AC Output Breakers - 200A   | Integrated                  |
| Surge Protection  | DC Type II / AC Type<br>III |