



**48 to 12 VDC Isolated Converter
Model 848HS
Step-Down Sealed DC-DC Converter**

Design Features

- Wide Range Input Voltage
- High Efficiency Design
- Hi Ingress Rating, IP 67
- Adjustable Output Voltage
- Optional Remote Output Voltage Sensing
- Optional Remote On/Off switching
- Low/High Input Voltage Cutouts
- Electronically Current Limited
- Thermally Protected
- Low No Load Power Consumption
- I/O Bayonet Quick Connection

		MODEL NO.	848-1260 HS
INPUT	NOMINAL INPUT VOLTAGE RANGE	46 to 56 VDC	
	MAXIMUM INPUT VOLTAGE RANGE	40 to 61 VDC	
	INPUT CURRENT WITH LOAD AT 60A; 13.0 Vout	19A with input at 48.0 V	
	INPUT CURRENT AT NO LOAD	< 160 mA over entire input and output ranges	
OUTPUT	OUTPUT VOLTAGE NOMINAL	13.0 +/- 0.1 VDC (factory adjusted)	
	OUTPUT VOLTAGE ADJUSTMENT RANGE	11.8 to 14.5 VDC (internally accessible to user)	
	OUTPUT LOAD REGULATION	200 mV (without remote sensing)	
		<30 mV (with remote sensing)	
	OUTPUT VOLTAGE REGULATION	< 0.2% with input excursions from 46-56 VDC	
	OUTPUT RIPPLE	50 mV RMS at maximum load (measured at 20% load)	
	MAXIMUM CONTINUOUS OUTPUT POWER	800 W	
	POWER SURGE	1000 W	
MAXIMUM LOAD CURRENT	60 ADC, for output voltage setting 11.7-13.2 V		
	EFFICIENCY	Not less than 94% over entire operating range	
PROTECTION	LOW INPUT VOLTAGE SHUTDOWN	40V +/- 1V	
	HIGH INPUT VOLTAGE SHUTDOWN	61V +/- 1V	
	OVERLOAD SHUTDOWN	Knee current limit starting at 110% of maximum load	
	ISOLATION	Input/Output-1800V, Input/Housing-2500V	
	OVER TEMPERATURE SHUTDOWN	Via internal thermostat, self resetting	
	COOLING	By conduction through base plate and convection	
	FUSING	Customer accessible by front panel removal	
CONNECTIONS	INPUT/ OUTPUT CONNECTION	Via 9 pin Bayonet connector (see owner's manual)	
	REMOTE TURN ON	Via pin H jumpered to -ve Pin I on input connector. Remote turn on may be disabled via internal jumper	
	REMOTE SENSE	Via 2 pins on the output connector. Remote sense usage is optional (see user manual)	
GENERAL	OPERATING TEMPERATURE RANGE	-40C to 70C, 100% loading	
	OPERATING HUMIDITY	100% non condensing	
	INGRESS RATING	IP 67	
	MOUNTING SLOT CENTERS (in./cm.)	10.0 x 7.3 / 25.4 x 18.5	
	DIMENSIONS, (in./cm.) (L x W x H)	15.5 x 8.0 x 2.9 / 39.4 x 20.3 x 7.4	
	HOUSING MATERIAL	All Aluminum	
	WEIGHT, (lb./kg.)	15 / 6.8	

NOTE: Specifications are subject to change without notice.

Rev 03/06/201



erter

verter

ig

r)
5C)
DC
n current
ion
nual)
ctor,

19

