



48 to 48 VDC Isolated Converter
Model 850HSBP
Regulated Sealed DC-DC Converter

Design Features

- Wide Range Input Voltage
- High Efficiency Isolated Design - 94%
- Hi Ingress Rating, IP 67
- Adjustable Output Voltage
- Optional Remote Output Voltage Sensing
- Optional Remote On/Off Switching
- Low/High Input Voltage Cutouts
- Electronically Current Limited
- Thermally Protected
- Low No Load Power Consumption
- I/O Bayonet Quick Connection

MODEL NO.		850HSBP
INPUT	NOMINAL INPUT VOLTAGE RANGE	44 to 70 VDC
	MAXIMUM INPUT VOLTAGE RANGE	75 VDC
	INPUT CURRENT WITH LOAD AT 18A; 48.0 Vout	19.1 A with input at 48.0 V
	INPUT INRUSH CURRENT AT FULL LOAD	Limited to 25A
	INPUT CURRENT AT NO LOAD	< 160 mA over entire input and output ranges
OUTPUT	OUTPUT VOLTAGE NOMINAL	48.0 +/- 0.1 VDC (factory adjusted)
	OUTPUT VOLTAGE ADJUSTMENT RANGE	46.0 to 54.0 VDC (internally accessible to user)
	OUTPUT LOAD REGULATION	200 mV (without remote sensing)
		<30 mV (with remote sensing 5%-100% Load)
	OUTPUT VOLTAGE REGULATION	< 0.2% with input excursions from 46-56 VDC
	OUTPUT RIPPLE	50 mV RMS at maximum load (measured at 25C)
	MAXIMUM CONTINUOUS OUTPUT POWER	864 W
	POWER SURGE	1000 W
PROTECTION	MAXIMUM LOAD CURRENT	18 ADC, for output voltage setting 46.0-70.0 VDC
	EFFICIENCY	Not less than 94% over entire operating range
	LOW INPUT VOLTAGE SHUTDOWN	40V +/- 1V
	HIGH INPUT VOLTAGE SHUTDOWN	60V +/- 1V
	OVERLOAD SHUTDOWN	Knee current limit starting at 110% of maximum current
	ISOLATION	Input/Output-1800V, Input/Housing-2500V
	OVER TEMPERATURE SHUTDOWN	Via internal thermostat, self resetting
CONNECTIONS	COOLING	By conduction through base plate and convection
	FUSING	Customer accessible by front panel removal
	INPUT/ OUTPUT CONNECTION	Via 9 pin Bayonet connector (see owner's manual)
	REMOTE TURN ON	Via pin H jumpered to -ve Pin I on input connector, may be disabled via internal jumper
GENERAL	REMOTE SENSE	Via 2 pins on the output connector usage is optional (see user manual)
	OPERATING TEMPERATURE RANGE	-40C to 70C, 100% loading
	OPERATING HUMIDITY	100% non condensing
	INGRESS RATING	IP 67
	MOUNTING SLOT CENTERS (in./cm.)	10.0 x 7.3 / 25.4 x 18.5
	DIMENSIONS, (in./cm.) (L x W x H)	15.5 x 8.0 x 2.9 / 39.4 x 20.3 x 7.4
	HOUSING MATERIAL	All Aluminum
	WEIGHT, (lb./kg.)	15 /6.8

NOTE: Specifications are subject to change without notice.

Rev 12/06/2023