



## CSW-24 SERIES INVERTER

### 24V Sine Wave on the Go



Pure  
Sine  
Wave



Battery  
Voltage  
Options



Continuous  
Output  
Options

#### Model Numbers

- CSW2024

#### Available For

- Emergency Medical Services
- Marine Systems
- Military Vehicles
- RV Systems
- Trucks
- Utility Vehicles

#### Available Accessories

- Remote Switch (CSW-RS)

The Magnum-Dimensions CSW-24 Series inverter from Sensata Technologies is a pure sine wave inverter designed to be powerful, yet simple to operate. The CSW will provide you with reliable AC power for troublefree use.

### FEATURES

#### Compact and Lightweight

The CSW provides pure sine wave power from a small footprint designed to fit in tight vehicle and marine spaces. And it is lightweight, so won't weigh you down.

#### At-a-Glance Status

The inverter's status can be determined at a glance with the easy to read LED light.

#### Digital Display

The alphanumeric display shows the inverter's battery voltage, total AC output power, along with additional operation codes.

#### USB Port

Power and charge your USB-enabled device with the available USB port.

#### GFCI AC Outlet

Plug in two pieces of equipment directly to the CSW and know that the GFCI outlet will quickly stop the flow of electricity should a ground fault occur. The outlet also comes with an LED indicator and test/reset capability.

### OPTIONS



#### Remote Switch

Use the optional CSW-RS remote switch for even easier on/off access away from the inverter. The CSW-RS comes with a 20' cable.

# CSW-24 SERIES SPECIFICATIONS



CSW2024

## INVERTER SPECIFICATIONS - OUTPUT

Continuous power at nominal DC voltage	2000 watts
Peak surge power	4000 watts
AC output voltage at 24.0 VDC	120 VAC $\pm$ 5%
AC output current	16.6 AAC
AC output frequency	60 Hz $\pm$ 0.5 Hz
AC output waveform	Pure sine wave
Total harmonic distortion (THD)	< 3%
USB	5V, 2.1 A

## INVERTER SPECIFICATIONS - INPUT

Nominal DC input voltage	25.0 VDC
DC input voltage range	21.0 - 31.0 VDC
Input current	97 DCA
No load draw - Power Save off	.8 ADC
No load draw - Power Save on	.3 ADC
Optimum efficiency	> 90%
High voltage shutdown	31.0 VDC
Low voltage alarm	22.4 VDC, audible
Low voltage shutdown	21.0 VDC

## GENERAL FEATURES AND CAPABILITIES

Transfer relay capability	NA
Display status indicator	LED: Status
Digital display	Input voltage, output power, warning, and error code
AC receptacles	NEMA 5-20 (GFCI)
Listings	Conforms to UL458, Certified to CSA 22.2, 107.1
Warranty	One year

## ENVIRONMENTAL SPECIFICATIONS

Operating temperature	0° C to +40° C (32° F to 104° F)
Nonoperating temperature	-20° C to +60° C (-4° F to 140° F)
Operating humidity	0 to 90% RH non condensing
Max operating altitude	9843' (3000 m) above sea level

## PHYSICAL SPECIFICATIONS

Dimensions (l x w x h)	16.3" x 9.1" x 4.3" (41.4 cm x 23.1 cm x 10.9 cm)
Shipping dimensions (l x w x h)	19" x 11.3" x 6.7" (48.3 cm x 28.7 cm x 17 cm)
Mounting	Shelf (top or bottom up) or bulkhead (DC terminals MUST be facing up)
Weight	11.5 lb (5.2 kg)
Shipping weight	13 lb (5.9 kg)



The World Depends on Sensors and Controls

### OFFICES

2211 West Casino Road  
Everett, Washington 98204 USA

425-353-8833

4467 White Bear Pkwy  
St. Paul, MN 55110 USA

800-553-6418

[www.SensataPower.com](http://www.SensataPower.com)

Testing for specifications at 25° C.  
Specifications subject to change without notice.

November 2017

Rev A

Part #64-0680