

Solis-(50-66)K-US-F

Solis Three Phase US Inverters



Features:

- ▶ Max. efficiency 98.8% (CEC efficiency 98.4%) with ultra-low start up voltage
- ▶ Compact and lightweight design inside a corrosion-resistant NEMA 4X enclosure
- ▶ Designed for all commercial, industrial, and utility-scale applications
- ▶ Transformer-less three phase design with 480 Vac output
- ▶ Wide voltage range and low startup voltage
- ▶ Industry-leading 4 MPPT designs with fast (<5 sec.) MPPT response times
- ▶ Integrated Arc Fault Circuit Interrupt (AFCI) option
- ▶ RS-485 Modbus communication protocol with Wi-Fi interface
- ▶ Web-based data monitoring with downloadable Solis Mobile App
- ▶ 10 years standard warranty with extension options



Ordering: Solis-(50-66K)-US-F

- LSW-SPRT (SunSpec MLRSD Transmitter)
- LSW-RSS (Tigo MLRSD Transmitter)
- SW (No Transmitter)

Datasheet

| Model Name | Solis-50K-US-F-XX* | Solis-60K-US-F-XX* | Solis-66K-US-F-XX* |
|---|--|--------------------|--------------------|
| Input DC | | | |
| Max. input voltage | 1000 V | | |
| Rated voltage | 720 V | | |
| Start-up voltage | 200 V | | |
| MPPT voltage range | 200-850 V | | |
| Max. input current | 4*28.5 A | | |
| Max. short circuit current | 4*55 A | | |
| MPPT number/Max. input strings number | 4/16 | | |
| Output AC | | | |
| Rated output power | 50 kW | 60 kW | 66 kW |
| Max. apparent output power | 50 kVA | 60 kVA | 66 kVA |
| Max. output power | 50 kW | 60 kW | 66 kW |
| Rated grid voltage | 3Φ/PE, 480 V | | |
| Rated grid frequency | 60 Hz | | |
| Max. output current | 60.2 A | 72.2 A | 79.4 A |
| Power Factor | >0.99 (0.8 leading - 0.8 lagging) | | |
| THDi | <3% | | |
| Efficiency | | | |
| Max. efficiency | 98.8% | | |
| CEC efficiency | 98.4% | | |
| Protection | | | |
| DC reverse-polarity protection | Yes | | |
| Ground fault monitoring | Yes | | |
| Anti-islanding protection | Yes | | |
| Integrated AFCI (DC arc-fault circuit protection) | Yes | | |
| Integrated DC switch | Yes | | |
| Rapid shutdown | Yes | | |
| General Data | | | |
| Dimensions (W*H*D) | SW: 24.9*40.4*14.7 in (633*1027*374 mm), LSW: 24.9*47.5*14.7 in (633*1206*374 mm) | | |
| Weight (inverter/wiring box) | SW: 147 lbs (66.7 kgs)/35.4 lbs (16 kgs), LSW: 147 lbs (66.7 kgs)/43.4 lbs (19.7 kgs) | | |
| Topology | Transformerless | | |
| Self consumption (night) | <1 W | | |
| Relative humidity | 0-100% | | |
| Operating ambient temperature range | -13°F to 140°F (-25°C to 60°C) | | |
| Storage environment | -13°F to 176°F (-25°C to 80°C) | | |
| Ingress protection | TYPE 4X | | |
| Cooling concept | Intelligent redundant fan-cooling | | |
| Max. operation altitude | 13,120 ft (4000 m) | | |
| Compliance | UL 1741, IEEE 1547, UL 1699B, UL 1998, FCC, UL 1741SA, California Rule 21, SRD-UL1741, CAN/CSA C22.2 107.1-1 | | |
| Features | | | |
| DC connection | 4 knockout for 2" conduit at bottom and side, Fuse screw terminal (Copper 12-6AWG) | | |
| AC connection | 4 knockout for 2" conduit at bottom and side, OT terminal (Copper or aluminum 8-2AWG) Aluminum requires bi-metallic compatible terminal | | |
| Display | LCD | | |
| Communication | Modbus RTU (Sunspec compliant), RS485, Optional: Cellular, Wi-Fi | | |

* Ordering guidelines: Determine the basic model from above and add your desired features as described on PG1
Ex: Solis-50K-US-F-LSW-SPRT, (inverter internal Sunspec transmitter)