

# Enphase Encharge 3T

The **Enphase Encharge 3T™** all-in-one AC-coupled storage system is **reliable, smart, simple, and safe**. It has a total usable energy capacity of 3.36 kWh and includes four embedded grid-forming microinverters with 1.28 kW power rating. It provides backup capability and installers can quickly design the right system size to meet the needs of both new and retrofit solar customers.



## Reliable

- Proven high-reliability IQ Series Microinverters
- Ten-year limited warranty
- Four embedded IQ8X-BAT Microinverters
- Passive cooling (no moving parts/fans)

## Smart

- Grid-forming capability for backup operation
- Remote software and firmware upgrade
- Mobile app-based monitoring and control
- Support for self consumption
- Utility time of use (TOU) optimization

## Simple

- Fully integrated AC battery system
- Quick and easy plug-and-play installation
- Interconnects with standard household AC wiring

## Safe

- Battery safety tested
- Lithium iron phosphate (LFP) chemistry for maximum safety and longevity

<b>MODEL NUMBER</b>	
ENCHARGE-3T-1P-NA	Encharge 3T battery storage system with integrated Enphase IQ Series microinverters and battery management unit (BMU). Includes: - One Encharge 3T™ base unit (B03-T01-US00-1-3) - One Encharge 3T™ cover kit with cover and wall mounting bracket (B03T-C-0430-0)
<b>OUTPUT (AC)</b>	
	<b>@240 VAC<sup>1</sup></b>
Rated (continuous) output power	1.28 kVA
Peak output power	1.92 kVA (10 seconds)
Nominal voltage / range	240/211–264 VAC
Nominal frequency / range	60/57–63 Hz
Rated output current	5.3 A
Peak output current	8.2A (10 seconds)
Power factor (adjustable)	0.85 leading ... 0.85 lagging
Maximum units per 20 A branch circuit	Three units (single phase)
Interconnection	Single phase
Maximum AC short circuit fault current over 3 cycles	23.2 Arms
Round trip efficiency <sup>2</sup>	89%
<b>BATTERY</b>	
Total capacity	3.5 kWh
Usable capacity	3.36 kWh
Round trip efficiency	96%
Nominal DC voltage	67.2 V
Maximum DC voltage	75.6 V
Ambient operating temperature range	-15° C to 55° C (5° F to 131° F) non-condensing
Optimum operating temperature range	0° C to 30° C (32° F to 86° F)
Chemistry	Lithium iron phosphate (LFP)
<b>MECHANICAL DATA</b>	
Dimensions (WxHxD)	430 x 775 x 188 mm (16.9 x 30.5 x 7.4 in)
Weight	One individual 40.5 kg (89.3 lbs) base unit plus 8.3 kg (18.3 lbs) cover and mounting bracket; total 48.8 kg (107.6 lbs)
Enclosure	Outdoor – NEMA 3R
IQ8X-BAT microinverter enclosure	NEMA type 6
Cooling	Natural convection – No fans
Altitude	Up to 2500 meters (8200 feet)
Mounting	Wall mount
<b>FEATURES AND COMPLIANCE</b>	
Compatibility	Compatible with grid-tied PV systems. Compatible with Enphase M Series and IQ Series Micros, Enphase Enpower, and Enphase IQ Envoy for backup operation.
Communication	Wireless 2.4 GHz
Services	Backup, self-consumption, TOU, Demand Charge, NEM Integrity
Monitoring	Enlighten Manager and MyEnlighten monitoring options; API integration
Compliance	UL 9540, UN 38.3, UL 9540A, UL 1998, UL 991, NEMA Type 3R, AC156 EMI: 47 CFR, Part 15, Class B, ICES 003 Cell Module: UL 1973, UN 38.3 Inverters: UL 62109-1, IEC 62109-2, UL 1741SA, CAN/CSA C22.2 No. 107.1-16, and IEEE 1547
<b>LIMITED WARRANTY</b>	
Limited Warranty <sup>3</sup>	>70% capacity, up to 10 years or 4000 cycles

1. Supported in both grid-connected and backup/off-grid operation.
2. AC to battery to AC at 50% power rating.
3. Whichever occurs first. Restrictions apply.

To learn more about Enphase offerings, visit [enphase.com](https://enphase.com)