



IQ8 Commercial Microinverters

The high-powered, smart grid-ready Enphase IQ8P-3P and IQ8H-3P Microinverters are specifically designed for 120/208 VAC (4-wire) three-phase interconnection for small commercial solutions.

Each microinverter integrates with the IQ Gateway Commercial 2 and the Enphase App monitoring and analysis software.

With simplified design, improved energy harvesting, and advanced monitoring, microinverters offer true peace of mind during operation and maintenance.

Enphase
25
year limited
warranty

The IQ Series Microinverters extend the reliability standards set forth by previous generations and undergo over a million hours of power-on testing, enabling Enphase to provide an industry-leading limited warranty of up to 25 years.*

Easy to install

- Lightweight and compact with plug-and-play connectors
- Power line communication (PLC) between components
- Faster installation

High productivity and reliability

- More than one million cumulative hours of testing
- Class II double-insulated enclosure
- Optimized for the latest high-powered PV modules

Smart grid-ready

- Complies with the latest advanced grid support
- Remote automatic updates for the latest grid requirements
- Configurable to support a wide range of grid profiles
- Meets IEEE® 1547 (UL 1741-SB) requirements

* 25-year warranty is valid, provided an internet-connected IQ Gateway is installed.

IQ8 Commercial Microinverters

| INPUT DATA (DC) | | UNITS | IQ8P-3P-72-E-US/IQ8P-3P-72-E-DOM-US ¹ | | IQ8H-3P-72-E-US ² | |
|---|----|-------------|--|-------------|------------------------------|--|
| Commonly used modules for pairing ³ | W | | 380–640 | | 320–540 | |
| Module compatibility ³ | — | | 54-cell/108-half-cell, 60-cell/120-half-cell, 66-cell/132-half-cell and 72-cell/144-half-cell | | | |
| Maximum input DC voltage | V | | 63 | | | |
| Peak power tracking voltage | V | | 35.5–53 | | 28.5–45 | |
| Operating range | V | | 16–63 | | | |
| Min./Max. start voltage | V | | 21/63 | | | |
| Max. DC continuous current (module I_{mp}) | A | | 14 | | | |
| Max. input DC short-circuit current | A | | 25 | | | |
| Max. DC short-circuit current (module I_{sc}) | A | | 20 | | | |
| Oversupply class DC ports | — | | II | | | |
| DC port backfeed current | A | | 0 | | | |
| PV array configuration | — | | 1×1 ungrounded array; no additional DC side protection required; AC side protection requires max. 20 A per branch circuit | | | |
| OUTPUT DATA (AC) | | UNITS | IQ8P-3P-72-E-US/IQ8P-3P-72-E-DOM-US ¹ | | IQ8H-3P-72-E-US ² | |
| Peak output power | VA | | 480 | | 384 | |
| Maximum continuous output power | VA | | 475 | | 380 | |
| Nominal (L-L) voltage/range ⁴ | V | 208/183–229 | 220/198–242 | 208/183–229 | 220/198–242 | |
| Maximum continuous output current | A | 2.28 | 2.16 | 1.83 | 1.73 | |
| Nominal frequency | Hz | | 60 | | | |
| Extended frequency range | Hz | | 47–68 | | | |
| Maximum microinverters per 20 A three-phase branch circuit ⁵ | — | | 12 | | 15 | |
| Oversupply class AC port | — | | III | | | |
| Power factor setting | — | | 1.0 | | | |
| Power factor (adjustable) | — | | 0.85 leading ... 0.85 lagging | | | |
| Total harmonic distortion | % | | <5 | | | |
| EFFICIENCY | | UNITS | IQ8P-3P-72-E-US/IQ8P-3P-72-E-DOM-US ¹ | | IQ8H-3P-72-E-US ² | |
| Peak efficiency | % | | 97.8 | | 97.7 | |
| CEC weighted efficiency | % | | 97.5 | | 96.5 | |
| MECHANICAL DATA | | | IQ8P-3P-72-E-US/IQ8P-3P-72-E-DOM-US ¹ | | IQ8H-3P-72-E-US ² | |
| Ambient temperature range | | | -40°F to 149°F (-40°C to 65°C) | | | |
| Relative humidity range | | | 4% to 100% (condensing) | | | |
| DC connector type ⁶ | | | Enphase EN4 bulkhead; ECA-EN4-S22-12:EN4 (TE PV4-S SOLARLOK) 150 mm/5.9" to Stäubli MC4 adapter cable pair (default supply) ⁷ | | | |
| Dimensions (H × W × D) | | | 10.4" × 7.9" × 1.4" (265 mm × 200 mm × 35 mm) without bracket | | | |
| Weight | | | 3.5 lb (1.6 kg) | | | |
| Cooling | | | Natural convection | | | |
| Approved for wet locations | | | Yes | | | |
| Enclosure | | | Class II double-insulated, corrosion-resistant polymeric enclosure | | | |
| Environmental category/UV exposure rating | | | Outdoor—NEMA Type 6/IP67 | | | |

| FEATURES | IQ8P-3P-72-E-US/IQ8P-3P-72-E-DOM-US ¹ | IQ8H-3P-72-E-US ² |
|---------------|--|---|
| Communication | | Power line communication (PLC) |
| Monitoring | | Enphase App monitoring and analysis software. Both options require the installation of an IQ Gateway Commercial 2. |
| Compliance | | CA Rule 21 (UL 1741-SB), UL 62109-1, UL 1741/IEEE 1547, FCC Part 15 Class B, ICES-0003 Class B, CAN/CSA-C22.2 NO. 107.1-01. This product is UL Listed as PV rapid shutdown equipment and conforms with NEC 2014, NEC 2017, and NEC 2020 section 690.12 and C22.1-2018 Rule 64-218 rapid shutdown of PV systems for AC and DC conductors, when installed according to manufacturer's instructions. |

¹IQ8P-3P-72-E-DOM-US is made in the United States of America. The PCBA, electrical parts, and enclosure are domestically manufactured to meet the eligibility requirements for the ITC domestic content bonus adder.

²IQ8H-3P-72-E-US is no longer being manufactured.

³Pairing PV modules with wattage above the limit may result in additional clipping losses. See the compatibility calculator at <https://link.enphase.com/module-compatibility>.

⁴Nominal voltage range can be configured if required by the utility. For interconnection to system voltages other than 120/208 VAC (4-wire) three-phase, a transformer is required to connect to the grid.

⁵Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area.

⁶Enphase IQ8P-3P and IQ8H-3P Microinverter bulkhead and adapter cable male/female DC connectors must only be mated with the identical type and manufacturer brand of male/female connectors.

⁷Qualified per UL subject 9703.

Revision history

| REVISION | DATE | DESCRIPTION |
|---------------|---------------|--|
| DSH-00236-7.0 | November 2025 | Added “Total harmonic distortion” information. |
| DSH-00236-6.0 | April 2025 | Added a new footnote to SKU IQ8H-3P-72-E-US stating that it is no longer being manufactured. |
| DSH-00236-5.0 | October 2024 | Removed the reference for preliminary testing for IQ8P-3P-72-E-DOM-US SKU. |
| DSH-00236-4.0 | August 2024 | Added information about IQ8P-3P-72-E-DOM-US. |
| DSH-00236-3.0 | February 2024 | Modified “208V three-phase” to “208Y VAC three-phase on page 1. |
| DSH-00236-2.0 | November 2023 | Updated the specifications. |
| DSH-00236-1.0 | October 2023 | Initial release. |