

## LITHIUM IRON PHOSPHATE BATTERY

### ELECTRICAL PERFORMANCE

Nominal Voltage	12.8V
Nominal Capacity	206Ah
Energy	2636.8Wh
Self Discharge	<3% / Month
Cells	3.2V 280Ah Cell

### CHARGE PERFORMANCE

Recommended Charge Current	40A
Maximum Charge Current	50A
Recommended Charge Voltage	14.4V-14.6V
BMS Charge Cut-Off Voltage	<14.6V
Reconnect Voltage	>14.4V
Balancing Voltage	<14.4V
Maximum Batteries in Series	4
Maximum Batteries in parallel	10

### DISCHARGE PERFORMANCE

Maximum Continuous Discharge Current	100A
Peak Discharge Current	200A(3S)
BMS Discharge Cut-Off Current	330 A
Recommended Low Voltage Disconnect	11.2V
BMS Discharge Cut-Off Voltage	>10.4 V
Reconnect Voltage	>11.6V
Short Circuit Protection	200 ~ 500

### TEMPERATURE PERFORMANCE

Discharge Temperature	-4 ~ 140 °F (-20 ~ 60 °C)
Charge Temperature	32 to 113 °F (0 to 45 °C)
Storage Temperature	23 to 95 °F (-5 to 35 °C)
BMS High Temperature Cut-Off	149 °F (65 °C)
Reconnect Temperature	131 °F (55 °C)

### COMPLIANCE

Certifications	UL1973 for Battery UL9540A, IEC62619 for Battery Cells. MSDS for Shipping
----------------	---



### MECHANICAL PERFORMANCE

Dimension (L x W x H)	10.83*7.78*11.22inches
Approx. Weight	47.6 lbs
Terminal Type	M8
Terminal Torque	80 ~ 100 in-lbs (9 ~ 11 N-m)
Case Material	Black Paint Plastic Case
Enclosure Protection	IP50

Performance may vary depending on application. All specifications are subject to change without prior notice to the user. This data is for evaluation purposes only. No guarantee is intended or implied by this data. For clarification and updated information, please contact us.