

**Trailer Electrical Interface Model
UTC 2412B**

ISO 1185 Input (24V)



SAE 560 Output (12V)



**ISO 1185
Input (24V)**



**SAE 560
Output (12V)**

Design Features

- Wide Range Input Voltage
- High Efficiency Design
- Hi Ingress Rating, IP 676
- Low Voltage Cutout
- High Voltage Cutout
- Electronically Current Limited
- Thermally Protected
- Low No Load Power Consumption
- All Aluminum Anodized Housing
- 6 Point Mounting

Input/Output Function Table for UTC 2412B

Function	Color	(24 Volts)		X	(12 Volts)	Color	Function
		INPUT			OUTPUT		
		ISO 1185			JAE 560		
		Pin #			Pin #		
Ground	White	1	→	X	1	White	Ground
Left Side - Tail, Marker, Clearance, License Lights	Black	2	→	X	2	Black	Clearance, ID, Lights
Left Turn Sig.	Yellow	3	→	X	3	Yellow	Left Turn Sig.
Normal Stop Lights	Red	4	→	X	4	Red	Normal Stop Lights
Right Turn Signal	Green	5	→	X	5	Green	Right Turn Signal
Right Side - Tail, Marker, Clearance, License Lights	Brown	6	→	X	6	Brown	Tail, Marker, License Lights
Trailer Aux Power	Blue	7	→	X	7	Blue	Constant Power

INPUT VOLTAGE RANGE	21-30 VDC (nominal) Will withstand up to 36V
INPUT CURRENT	10A max. per Circuit
OUTPUT VOLTAGE	13.6 +, - 0.3 V per circuit
OUTPUT CURRENT	15A per line (BRN, BLK, RED, BLUE) 10A per line (YEL, GRN)
OUTPUT REGULATION	0.2V over entire input voltage and load current range

OPERATING TEMPERATURE	-40C to +60C
STORAGE TEMPERATURE	-60C to +125C
OVERLOAD PROTECTION	Electronic
EFFICIENCY	92% Typical
CONSTRUCTION	BLACK ANODIZED ALUMINUM
WEIGHT	14 lbs./ 6.5 kg. total

NOTE: Specifications are subject to change without notice.

Rev 7/15/2015