

AGM 12/160 (group 4D)



Product code: 62001600

AGM batteries

In AGM batteries, the electrolyte (mixture of water and sulphuric acid) is largely absorbed in glass fibre. This type of battery is entirely maintenance-free and there is no gas formation with normal use. Not requiring any ventilation, these batteries can be installed anywhere.

Their construction gives a very fast discharge at very high currents so AGM batteries are ideal for systems that require high currents (for instance when starting an engine). The battery poles can be unscrewed and this type of battery can be combined with every standard battery terminal.

- Excellent starter function.
- Perfect upgrade for wet lead acid batteries.
- Same initial power surge in an AGM 12/90 Ah as 180 Ah wet lead-acid battery.
- Glass-fibre technology ensures low internal resistance.
- Use of thicker plates extends lifespan.
- Also for medium cyclical use.
- Two-year warranty.

Specifications

General specifications

Nominal battery voltage	12 V
Nominal battery capacity C20 (battery capacity at a discharge time of 20 hours, till 10.5 V per battery)	160 Ah
Max. charge current	45 Ah
Battery terminals	M8
Max. outer dimensions (incl. terminals/grip handles), lxxh	485 x 170 x 242 mm 19.1 x 6.7 x 9.5 inch
Weight	42.3 kg 93.3 lb

Technical specifications

CCA to DIN	550 A
CCA to SAE	870 A