

AGM 6/400



Product code: 61004000

In AGM batteries, the electrolyte (mixture of water and sulphuric acid) is largely absorbed in glass fibre. This type of battery is entirely maintenance-free and there is no gas formation with normal use. Not requiring any ventilation, these batteries can be installed anywhere.

Their construction gives a very fast discharge at very high currents so AGM batteries are ideal for systems that require high currents (for instance when starting an engine). The battery poles can be unscrewed and this type of battery can be combined with every standard battery terminal.

- Offers an alternative solution in placement and dimensioning.
- Easy configuration of 12/24/48 V battery banks, with high capacity.
- Double pole for easy installation.
- No gas formation with normal use.
- Can be combined with every standard battery terminal.
- Two year warranty.

Specifications

General specifications

Nominal battery voltage	6 V
Nominal battery capacity C20 (battery capacity at a discharge time of 20 hours, till 10.5 V per battery)	400 Ah
Max. charge current	110 Ah
Battery terminals	A-type + stud M10
Max. outer dimensions (incl. terminals/grip handles), lxxh	295 x 180 x 428 mm 11.6 x 7.1 x 16.9 inch
Weight	53 kg 116.8 lb

Technical specifications

CCA to DIN	520 A
CCA to SAE	870 A