DC Distribution 500



Product code: 77020200



The DC Distribution 500 is the smallest distribution model available. It connects up to four DC devices to the DC groups, such as a battery charger, inverter, alternators and solar panels. With the included plug & play cable it can be easily connected to the MasterBus network.

The MasterView panel gives all fuses logical names to ensure you receive understandable error notifications (for example charger fuse defect).

The DC Distribution always comes with four ANL fuses: 80, 80, 125 and 160 A, and a spare fuse of 125 A. Replacement fuses and other amperages can be found <u>here</u>here.



Specifications

General specifications

MasterBus powering	no
Languages on display	ENG, NL, DE, SP, IT, FRA, FIN, SWE, DEN, NOR
Battery voltage	12, 24 or 48 V DC
Dimensions, hxwxd	150 x 216 x 65 mm
	5.9 x 8.5 x 2.6 inch
Weight	1.2 kg
	2.6 lb
Current	300 A cont. / 500 A for 5 minutes
Standard fuses	80, 80, 125, 160 A - ANL-type (deviating values can be ordered
	separately)
Spare fuse	125 A ANL type
Alarms	fuse monitoring
Delivered with	five fuses, hex tool, MasterBus terminator, MasterBus cable,
	cable protections for DC connections

Technical specifications

Protection degree

IP21

