

Three Phase Commercial Inverter

USA Domestic Content Eligible*

For North America

SE10KUS / SE17.3KUS / SE30KUS / SE40KUS

INVERTER



SolarEdge's USA-manufactured offering for C&I rooftops and carports

- / Eligible for domestic content*: SolarEdge's USA-manufactured inverters, when paired with certain SolarEdge USA-manufactured power optimizers, are intended to be eligible for the enhanced federal income tax credit for domestic content
- / Specifically designed to work with power optimizers
- / Quick and easy inverter commissioning directly from a smartphone using SolarEdge SetApp
- / Fixed DC voltage inverter for superior efficiency and longer strings
- / Small, lightest in its class, and easy to install outdoors or indoors on provided bracket
- / Built-in type 2 DC and AC Surge Protection, to better withstand lightning events
- / Integrated arc fault protection and rapid shutdown for NEC 2014 – 2023, per articles 690.11 and 690.12
- / Built-in module level monitoring with ethernet, wireless, or cellular communication for full system visibility
- / Integrated safety switch
- / UL 1741 SA and SB certified, for CPUC Rule 21 grid compliance

* For more details, see [Eligibility for Domestic Content](#) on last page..

Three Phase Commercial Inverter

USA Domestic Content Eligible for North America

SE10KUS / SE17.3KUS / SE30KUS / SE40KUS

Applicable to inverters with part number	xSE-SIN-USxxLxxxx				UNITS
Model Number	SE10KUS	SE17.3KUS	SE30KUS	SE40KUS	
OUTPUT					
Maximum AC Output Capacity	40,000				W
Rated AC Power Output	10,000	17,300	30,000	40,000	W
Maximum Apparent AC Output Power	10,000	17,300	30,000	40,000	VA
AC Output Line Connections	3W + PE, 4W + PE				
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-N)	105 – 120 – 132.5		244 – 277 – 305		Vac
AC Output Voltage Minimum-Nominal-Maximum ⁽¹⁾ (L-L)	183 – 208 – 229		422.5 – 480 – 529		Vac
AC Frequency Min-Nom-Max ⁽¹⁾	59.3 – 60 – 60.5		59.3 – 60 – 60.5		Hz
Maximum Continuous Output Current (per Phase)	27.8	48.25	36.25	48.25	Aac
GFDI Threshold	1				A
Utility Monitoring, Islanding Protection, Country Configurable Set Points	Yes				
Total Harmonic Distortion	≤ 3				%
Power Factor Range	+/- 0.85 to 1				
INPUT ⁽²⁾					
Maximum DC Power (Module STC)	17,500	30,275	52,500	70,000	W
Transformer-less, Ungrounded	Yes				
Maximum Input Voltage DC+ to DC-	600		1000		Vdc
Operating Voltage Range	370 – 600		840 – 1000		Vdc
Maximum Input Current	27.8	48.25	36.25	48.25	Adc
Maximum Input Short Circuit Current	55				Adc
Reverse-Polarity Protection	Yes				
Ground-Fault Isolation Detection	167kΩ Sensitivity ⁽³⁾				
CEC Weighted Efficiency	97	97.5	98.5		%
Night-time Power Consumption	<4				W
ADDITIONAL FEATURES					
Supported Communication Interfaces	2 x RS485, Ethernet, Cellular (optional)				
Inverter Commissioning	With the SetApp mobile application using built-in access point for local connection				
Arc Fault Protection	Integrated, User Configurable (According to UL 1699B)				
Photovoltaic Rapid Shutdown System	NEC 2014 – 2023, built-in, if paired with C651U				
RS485 Surge Protection Plug-in	Supplied with the inverter, built-in				
DC Surge Protection	Type II, field replaceable, built-in				
AC Surge Protection	Type II, field replaceable, built-in				
Smart Energy Management	Export Limitation				
DC SAFETY SWITCH					
DC Disconnect	Integrated				
STANDARD COMPLIANCE					
Safety	UL 1741; UL 1741 SA; UL 1741 SB; UL 1699B; CSA C22.2#107.1; Canadian AFCI according to T.I.L. M-07				
Grid Connection Standards	IEEE 1547-2018, Rule 21, Rule 14 (HI)				
Emissions	FCC Part 15 Class A				
INSTALLATION SPECIFICATIONS					
AC Output Conduit Size / AWG Range	¾" or 1" / 6 – 10 AWG				
DC Input Conduit Size / AWG Range	¾" or 1" / 6 – 12 AWG				
Number of DC Input Pairs (Fuseless)	3				
Dimensions with Safety Switch (H x W x D)	31.8 x 12.5 x 11.8 / 808 x 317 x 300				in / mm
Weight with Safety Switch	78.2 / 35.5				lb / kg
Cooling	Fans (user replaceable)				
Noise	< 62				dBA
Operating Temperature Range	-40 to +140 / -40 to +60 ⁽⁴⁾				°F / °C
Protection Rating	NEMA 3R				
Mounting	Bracket provided				

(1) For other regional settings please contact SolarEdge support.

(2) For compatibility of inverters and power optimizers, see this [technical note](#).

(3) Where permitted by local regulations.

(4) For power derating information, see the [Temperature Derating](#) technical note.

Three Phase Commercial Inverter

USA Domestic Content Eligible for North America

SE10KUS / SE17.3KUS / SE30KUS / SE40KUS

***Eligibility for Domestic Content**

As it relates to the domestic content rules, the U.S. Department of Treasury and the IRS have not yet issued proposed or final regulations. Rather, the IRS has issued three notices - Notice 2023-38, Notice 2024-41 and Notice 2025-08. These notices provide guidance regarding the domestic content rules. SolarEdge products referenced herein are manufactured with the intent to be eligible for inclusion under the elective safe harbor table in calculating the Domestic Cost Percentage under the "Rooftop (MLPE)" category (under IRS Notices 2024-41 and 2025-08, depending on the PN used – see chart below). Eligibility is subject to the installation of qualified USA-Manufactured inverters and Power Optimizers (C651U) in the same project. SolarEdge does not provide tax and/or legal advice. You should consult with your own legal and/or tax advisor(s) regarding the eligibility of your project for the ITC or PTC, including the 10% Domestic Content bonus, to determine how the applicable rules apply to your project. The forward-looking statements in this document are accurate as of the date herein and are subject to change. For more information, please contact your local SolarEdge sales representative.

PN	Domestically produced MPCs per notice 2024-41*	Domestically produced MPCs per notice 2025-08*
USE-SIN-USR0IBNS6, when paired with C651U	Printed Circuit Board Assemblies, Electrical Parts, Enclosure (35.6%)	Printed Circuit Board Assemblies (DC-DC) and (AC-AC), Enclosure, Production (24.8%)
USE-SIN-USR0IBNS8, when paired with C651U	Printed Circuit Board Assemblies, Enclosure, (17.6%)	Printed Circuit Board Assemblies (DC-DC) and (AC-AC), Enclosure, Production (24.8%)

SolarEdge is a global leader in smart energy technology. By leveraging world-class engineering capabilities and with a relentless focus on innovation, SolarEdge creates smart energy solutions that power our lives and drive future progress.

SolarEdge developed an intelligent inverter solution that changed the way power is harvested and managed in photovoltaic (PV) systems. The SolarEdge DC optimized inverter maximizes power generation while lowering the cost of energy produced by the PV system.

Continuing to advance smart energy, SolarEdge addresses a broad range of energy market segments through its PV, storage, EV charging, UPS, and grid services solutions.

-  SolarEdge
-  @SolarEdgePV
-  @SolarEdgePV
-  SolarEdgePV
-  SolarEdge
-  www.solaredge.com/corporate/contact

solaredge.com

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREGE, the SolarEdge logo, OPTIMIZED BY SOLAREGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: April 10, 2025 DS-000246-NAM Subject to change without notice.

Cautionary Note Regarding Market Data and Industry Forecasts: This brochure may contain market data and industry forecasts from certain third-party sources. This information is based on industry surveys and the preparer's expertise in the industry and there can be no assurance that any such market data is accurate or that any such industry forecasts will be achieved. Although we have not independently verified the accuracy of such market data and industry forecasts, we believe that the market data is reliable and that the industry forecasts are reasonable.

