


This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

<b>Applicant:</b>	SimpliPhi Power Inc.	<b>Manufacturer:</b>	SimpliPhi Power Inc.
<b>Address:</b>	3100 Camino Del Sol, Oxnard, Ca 93030	<b>Address:</b>	3100 Camino Del Sol, Oxnard, Ca 93030
<b>Country:</b>	USA	<b>Country:</b>	USA
<b>Contact:</b>	Dumindra De Zoysa, Zak Wellman	<b>Contact:</b>	Dumindra De Zoysa, Zak Wellman
<b>Phone:</b>	805-640-6700 Ext 407	<b>Phone:</b>	805-640-6700 Ext 407
<b>FAX:</b>	805-624-4057	<b>FAX:</b>	805-624-4057
<b>Email:</b>	dumindradz@simpliphipower.com zakw@simpliphipower.com	<b>Email:</b>	dumindradz@simpliphipower.com; zakw@simpliphipower.com

**Party Authorized To Apply Mark:** Same as Manufacturer  
**Report Issuing Office:** 3933 US Route 11 Cortland, NY 13045

**Control Number:** 5004007      **Authorized by:**   
 for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.  
 545 East Algonquin Road, Arlington Heights, IL 60005  
 Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

<b>Standard(s):</b> Energy Storage Systems and Equipment [ANSI/CAN/UL 9540:2016 Ed.1]
<b>Product:</b> Energy Storage System
<b>Brand Name:</b> SimpliPhi Power

0PHI-; may be followed by BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12; may be followed by BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12; may be followed by BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12; may be followed by BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12; may be followed by -MNCB or -BSSCB.

**Models:**

A-, 2A-, 3A-; followed by 4PHI-, 5PHI-, 6PHI-; may be followed by BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12; may be followed by BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12; may be followed by BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12 may be followed by -MNCB or -BSSCB.

## 7.0 Illustrations

### Illustration 6 - Model Similarity

Model Example	Descriptions
0PHI-YYYY	Sol-Ark External to Cabinet with BOSS Enclosure/s
0PHI-YYYY-Z	Sol-Ark External to Enclosure with BOSS Enclosure/s and Combiner Box
A-XPHI	AccESS Unit Alone, Can house 4, 5, or 6 Batteries
A-XPHI-YYY	AccESS Unit with BOSS Enclosure/s
A-XPHI-YYY-Z	AccESS Unit with BOSS Enclosure/s and Combiner Box
2A-XPHI-Z	Qty 2 AccESS Unit with Combiner Box
2A-XPHI-YYY-Z	Qty 2 AccESS unit with BOSS Enclosure/s and Combiner Box
3A-XPHI-Z	Qty 3 AccESS Unit with Combiner Box
3A-XPHI-YYY-Z	Qty 3 AccESS Unit with BOSS Enclosure/s and Combiner Box

#### A= Number of AccESS Enclosures

A = (A), (2A), (3A), or blank

#### X= Number of Batteries in the AccESS Enclosure

X = 4, 5, 6 or 0

#### Y= BOSS Enclosure/s can have multiples within the model nomenclature

Y= BOSS-6-R-3, BOSS-6-R-4, BOSS-6-R-5, BOSS-6-6, BOSS-12-8, BOSS-12-9, BOSS-12-10, BOSS-12-12, or blank.

#### Z = Combiner Boxes

Z= MNCB, BSSCB, or blank.

#### AccESS Enclosure Descriptions

A-4PHI-SA-12-R: Maximum Rated Capacity 15.48 kWh

A-5PHI-SA-12-R: Maximum Rated Capacity 19.35 kWh

A-6PHI-SA-12: Maximum Rated Capacity 23.22 kWh

#### BOSS Enclosure

BOSS-6-R-3: Maximum Rated Capacity 11.61 kWh

BOSS-6-R-4: Maximum Rated Capacity 15.48 kWh

BOSS-6-R-5: Maximum Rated Capacity 19.35 kWh

BOSS-6-6: Maximum Rated Capacity 23.22 kWh

BOSS-12-8: Maximum Rated Capacity 30.96 kWh

BOSS-12-9: Maximum Rated Capacity 34.83 kWh

BOSS-12-10: Maximum Rated Capacity 38.7 kWh

BOSS-12-12: Maximum Rated Capacity 46.44 kWh